

Spannschloss, Gabel/Gabel Ropeblock



Produktinformation

Allgemein:

- Feuerverzinkt
- Inklusive Sicherungsmutter
- Hochfester Stahl (geschmiedet)
- MBL = 5x WLL

Artikel-Nr.	Tragfähigkeit t		L min.	L max.	A mm	P mm	U (mm)	W mm	Gewicht (kg)	Lieferzeit (in Tagen)
422100230200	0,23	6.35 x 102	175	277	121	6	15	11	0,16	30
422100360200	0,36	7.94 x 114	212	314	138	6	22	13	0,24	30
422100540200	0,54	9.53 x 152	258	410	181	8	22	14	0,37	30
422100100200	1	12.7 x 152	292	470	190	10	27	16	0,71	14
422100100205	1	12.7 x 229	368	622	266	10	27	16	0,79	30
422100100206	1	12.7 x 305	445	775	343	10	27	15	1,09	14
422100160200	1,59	15.9 X 152	325	509	200	13	33	20	1,23	30
422100160205	1,59	15.9 X 229	401	662	276	13	33	20	1,56	30

422100160206	1,59	15.9 x 305	478	814	353	13	33	20	1,77	30
422100240200	2,36	19.1 X 152	356	546	210	16	38	24	1,86	30
422100240205	2,36	19.1 x 229	432	699	286	16	38	24	2,48	30
422100240206	2,36	19.1 X 305	508	851	362	6	38	24	2,98	14
422100240207	2,36	19.1 x 457	660	1.156	514	16	38	24	3,64	30
422100330200	3,27	22.2 x 305	543	892	370	19	44	29	3,71	30
422100330205	3,27	22.2 x 457	695	1.197	523	19	44	29	4,89	30
422100450205	4,54	25.4 X 152	425	628	228	22	52	34	4,62	30
422100450207	4,54	25.4 x 305	577	933	380	22	52	34	5,53	30
422100450206	4,54	25.4 x 457	729	1.237	532	22	52	34	6,87	30
422100450200	4,54	25.4 x 610	882	1.542	685	22	52	34	8,2	14
422100690200	6,89	31.8 X 305	644	1.012	384	28	71	44	9,34	30
422100690205	6,89	31.8 x 45	796	1.317	537	28	71	44	11,2	30
422100690206	6,89	31.8 610	948	1.622	689	28	71	44	12,8	30
422100970200	9,71	38.1 x 305	673	1.073	400	35	71	52	13,9	30
422100970205	9,71	8.1 x 457	826	1.359	553	35	71	52	16,7	30
422100970206	9,71	38.1 x 610	978	1.664	705	35	71	52	18,9	30
422101270200	12,7	44.5 X 457	899	1.356	8	41	86	66	24,5	30
422101270205	12,7	44.5 X 610	51	1.661	721	41	86	66	28,7	30
422101680200	16,8	51.0 x 610	1.157	1.766	38	51	94	66	46,5	30
422102720200	27,2	63.5 x 610	1.244	1.854	9	57	113	76	75	30
422103400200	34	70.0 x 610	1.289	1.899	-	70	106	92	90	30

Blaupause

