



Electric Rope Hoist MINIFOR™ TR125 SY

Product information

The Minifor™ TR125 SY hoist is equipped with a special synthetic rope. It can be used to lift over great heights (standard rope length up to 200 m, longer ropes upon request). The torque is steady and speed is also stable at 30 m/min. The motor integrated brake makes it intrinsically safe in operation. The Minifor™ TR125 SY hoist is available with different voltages and is suitable for various applications. It is operated through a push button pendant control.

Options:

- Plugin pendant control + 10, 15 or 25 m extensions cable.
- Radio remote control.
- Synthetic rope with hook 20 m. Other lengths on request.
- Plastic storage box.
- Combi Pro bag for rope storage.
- Reeler for rope storage.

Note: Excl. wire (to be ordered separately).

| Part Code | WLL ton | Speed m/min | Tension (V) | Frequency Hz | Nominal current (A) | a mm | b mm | c mm | d min. | e mm | f mm | g mm | h mm | i mm | j mm | k mm | l mm | Weight kg | Delivery time |
|-----------|---------|-------------|-------------|--------------|---------------------|------|------|------|--------|------|------|------|------|------|------|------|------|-----------|---------------|
| 5406 | 0.125 | 30 | 400 | 50 | 2.25 | 427 | 15 | 140 | 728 | 209 | 100 | 20 | 20 | 324 | 356 | 112 | 15 | 20 | 30 |
| 5406 | 0.125 | 30 | 230 | 50 | 6.2 | 427 | 15 | 140 | 728 | 209 | 100 | 20 | 20 | 324 | 356 | 112 | 15 | 20 | 30 |
| 5406 | 0.125 | 15 | 230 | 50 | 3.9 | 427 | 15 | 140 | 728 | 209 | 100 | 20 | 20 | 324 | 356 | 112 | 15 | 21 | 30 |
| 5406 | 0.125 | 15 | 115 | 50/60 | 9 | 427 | 15 | 140 | 728 | 220 | 100 | 20 | 20 | 324 | 356 | 112 | 15 | 21 | 30 |
| 5406 | 0.125 | 30 | 690 | 50 | 1.3 | 427 | 15 | 140 | 728 | 259 | 158 | 20 | 20 | 324 | 375 | 112 | 15 | 22 | 30 |

Blueprint

