

Lifting Beam T-A-SL

Product information



The lifting beam of the T-A-SL series has an eye suspension for single hooks according to DIN 15401 on the crane side and shackle bars on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry.

Material: Construction steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Part Code	WLL ton	Length m	H mm	L min. mm	L max. mm	S mm	T mm	W mm	Weight kg	Delivery time
6205TASL22000	2	1-2	135	1,000	2,000	50	20	65	56	49
6205TASL23000	2	1.5-3	135	1,500	3,000	50	20	65	94	49
6205TASL24000	2	2-4	135	2,000	4,000	50	20	65	148	49
6205TASL25000	2	2.5-5	135	2,500	5,000	50	20	65	250	49
6205TASL26000	2	3-6	135	3,000	6,000	50	20	65	295	49
6205TASL32000	3	1.04-2	150	1,040	2,000	60	25	75	71	49
6205TASL33000	3	1.56-3	150	1,560	3,000	60	25	75	138	49
6205TASL34000	3	2.08-4	150	2,080	4,000	60	25	75	210	49

6205TASL35000	3	2.6-5	150	2,600	5,000	60	25	75	305	49
6205TASL36000	3	3-6	150	3,000	6,000	60	25	75	429	49
6205TASL52000	5	1.1-2	170	1,100	2,000	90	25	85	111	49
6205TASL53000	5	1.56-3	170	1,560	3,000	90	25	85	179	49
6205TASL54000	5	2.02-4	170	2,020	4,000	90	25	85	265	49
6205TASL55000	5	2.66-5	170	2,660	5,000	90	25	85	447	49
6205TASL56000	5	3.12-6	170	3,120	6,000	90	25	85	608	49
6205TASL82000	8	1-2	210	1,000	2,000	100	30	105	166	49
6205TASL83000	8	1.6-3	210	1,600	3,000	100	30	105	262	49
6205TASL84000	8	2-4	210	2,000	4,000	100	30	105	373	49
6205TASL85000	8	2.6-5	210	2,600	5,000	100	30	105	608	49
6205TASL86000	8	3-6	210	3,000	6,000	100	30	105	784	49
6205TASL102000	10	1.08-2	240	1,080	2,000	115	40	120	182	49
6205TASL103000	10	1.62-3	240	1,620	3,000	115	40	120	314	49
6205TASL104000	10	2.16-4	240	2,160	4,000	115	40	120	433	49
6205TASL105000	10	2.7-5	240	2,700	5,000	115	40	120	692	49
6205TASL106000	10	3.01-6	240	3,010	6,000	115	40	120	910	49

Blueprint

