

Lifting Beam T-A-VR

Product information



The lifting beam of the T-A-VR series has an eye suspension for single hooks according to DIN 15401 on the crane side and adjustable lifting frames on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry.

Material: Construction steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Finish: RAL 3000 (flame red)

Standard: EN 13155

Part Code	WLL ton	Length m	H mm	L min. mm	L max. mm	S mm	T mm	W mm	Weight kg	Delivery time
6205TAVR22000	2	1-2	135	1,000	2,000	50	20	65	53	49
6205TAVR23000	2	1.5-3	135	1,400	3,000	50	20	65	100	49
6205TAVR24000	2	2-4	135	2,000	4,000	50	20	65	127	49
6205TAVR25000	2	2.5-5	135	2,500	5,000	50	20	65	197	49
6205TAVR26000	2	3-6	135	3,000	6,000	50	20	65	229	49
6205TAVR32000	3	1-2	150	1,000	2,000	100	25	75	76	49
6205TAVR33000	3	1.5-3	150	1,500	3,000	100	25	75	131	49
6205TAVR34000	3	2-4	150	2,000	4,000	100	25	75	165	49

6205TAVR35000	3	2.5-5	150	2,500	5,000	100	25	75	246	49
6205TAVR36000	3	3-6	150	3,000	6,000	100	25	75	297	49
6205TAVR52000	5	1-2	170	1,000	2,000	100	25	85	105	49
6205TAVR53000	5	1.5-3	170	1,500	3,000	100	25	85	167	49
6205TAVR54000	5	2-4	170	2,000	4,000	100	25	85	249	49
6205TAVR55000	5	2.5-5	170	2,500	5,000	100	25	85	363	49
6205TAVR56000	5	3-6	170	3,000	6,000	100	25	85	426	49
6205TAVR82000	8	1-2	210	1,000	2,000	100	30	105	151	49
6205TAVR83000	8	1.5-3	210	1,500	3,000	100	30	105	222	49
6205TAVR84000	8	2-4	210	2,000	4,000	100	30	105	326	49
6205TAVR85000	8	2.5-5	210	2,500	5,000	100	30	105	424	49
6205TAVR86000	8	3-6	210	3,000	6,000	100	30	105	642	49
6205TAVR102000	10	1-2	240	1,000	2,000	100	40	120	157	49
6205TAVR103000	10	1.5-3	240	1,500	3,000	100	40	120	252	49
6205TAVR104000	10	2-4	240	2,000	4,000	100	40	120	349	49
6205TAVR105000	10	2.5-5	240	2,500	5,000	100	40	120	524	49
6205TAVR106000	10	3-6	240	3,000	6,000	100	40	120	670	49

Blueprint

