

## Lifting Beam T-A-VR

### Product information



The lifting beam of the T-A-VR series has an eye suspension for single hooks according to DIN 15401 on the crane side and adjustable lifting frames on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry.

**Material:** Construction steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +100°C

**Finish:** RAL 3000 (flame red)

**Standard:** EN 13155

| Part Code     | WLL ton | Length m | H mm | L min. mm | L max. mm | S mm | T mm | W mm | Weight kg | Delivery time |
|---------------|---------|----------|------|-----------|-----------|------|------|------|-----------|---------------|
| 6205TAVR22000 | 2       | 1-2      | 135  | 1,000     | 2,000     | 50   | 20   | 65   | 53        | 49            |
| 6205TAVR23000 | 2       | 1.5-3    | 135  | 1,400     | 3,000     | 50   | 20   | 65   | 100       | 49            |
| 6205TAVR24000 | 2       | 2-4      | 135  | 2,000     | 4,000     | 50   | 20   | 65   | 127       | 49            |
| 6205TAVR25000 | 2       | 2.5-5    | 135  | 2,500     | 5,000     | 50   | 20   | 65   | 197       | 49            |
| 6205TAVR26000 | 2       | 3-6      | 135  | 3,000     | 6,000     | 50   | 20   | 65   | 229       | 49            |
| 6205TAVR32000 | 3       | 1-2      | 150  | 1,000     | 2,000     | 100  | 25   | 75   | 76        | 49            |
| 6205TAVR33000 | 3       | 1.5-3    | 150  | 1,500     | 3,000     | 100  | 25   | 75   | 131       | 49            |
| 6205TAVR34000 | 3       | 2-4      | 150  | 2,000     | 4,000     | 100  | 25   | 75   | 165       | 49            |

|                |    |       |     |       |       |     |    |     |     |    |
|----------------|----|-------|-----|-------|-------|-----|----|-----|-----|----|
| 6205TAVR35000  | 3  | 2.5-5 | 150 | 2,500 | 5,000 | 100 | 25 | 75  | 246 | 49 |
| 6205TAVR36000  | 3  | 3-6   | 150 | 3,000 | 6,000 | 100 | 25 | 75  | 297 | 49 |
| 6205TAVR52000  | 5  | 1-2   | 170 | 1,000 | 2,000 | 100 | 25 | 85  | 105 | 49 |
| 6205TAVR53000  | 5  | 1.5-3 | 170 | 1,500 | 3,000 | 100 | 25 | 85  | 167 | 49 |
| 6205TAVR54000  | 5  | 2-4   | 170 | 2,000 | 4,000 | 100 | 25 | 85  | 249 | 49 |
| 6205TAVR55000  | 5  | 2.5-5 | 170 | 2,500 | 5,000 | 100 | 25 | 85  | 363 | 49 |
| 6205TAVR56000  | 5  | 3-6   | 170 | 3,000 | 6,000 | 100 | 25 | 85  | 426 | 49 |
| 6205TAVR82000  | 8  | 1-2   | 210 | 1,000 | 2,000 | 100 | 30 | 105 | 151 | 49 |
| 6205TAVR83000  | 8  | 1.5-3 | 210 | 1,500 | 3,000 | 100 | 30 | 105 | 222 | 49 |
| 6205TAVR84000  | 8  | 2-4   | 210 | 2,000 | 4,000 | 100 | 30 | 105 | 326 | 49 |
| 6205TAVR85000  | 8  | 2.5-5 | 210 | 2,500 | 5,000 | 100 | 30 | 105 | 424 | 49 |
| 6205TAVR86000  | 8  | 3-6   | 210 | 3,000 | 6,000 | 100 | 30 | 105 | 642 | 49 |
| 6205TAVR102000 | 10 | 1-2   | 240 | 1,000 | 2,000 | 100 | 40 | 120 | 157 | 49 |
| 6205TAVR103000 | 10 | 1.5-3 | 240 | 1,500 | 3,000 | 100 | 40 | 120 | 252 | 49 |
| 6205TAVR104000 | 10 | 2-4   | 240 | 2,000 | 4,000 | 100 | 40 | 120 | 349 | 49 |
| 6205TAVR105000 | 10 | 2.5-5 | 240 | 2,500 | 5,000 | 100 | 40 | 120 | 524 | 49 |
| 6205TAVR106000 | 10 | 3-6   | 240 | 3,000 | 6,000 | 100 | 40 | 120 | 670 | 49 |

# Blueprint

