

## Lifting Beam T-K-SB

### Product information



The lifting beam of the T-K-SB series has a 2-strand chain suspension for single hooks according to DIN 15401 on the crane side and rigid shackle plates on the load side. The matching shackles are included in the scope of delivery. You are able to expand the lifting beam with additional equipment from our web shop. The lifting beam is supplied in the standard color RAL 3000 (flame red), other colors are also possible on request.

For other intermediate sizes and load capacities, you can also send us an inquiry.

**Material:** Construction steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +100°C

**Finish:** RAL 3000 (red flame)

**Standard:** EN 13155

Part Code	WLL ton	Length m	D mm	H mm	L min. mm	L max. mm	Ø T	W mm	Weight kg	Delivery time
6205TKSB22000	2	2	887	110	1,000	2,000	16	60	43	49
6205TKSB23000	2	3	1,159	110	1,500	3,000	16	60	72	49
6205TKSB24000	2	4	1,440	110	2,000	4,000	16	60	92	49
6205TKSB25000	2	5	1,714	110	2,500	5,000	16	60	147	49
6205TKSB26000	2	6	2,001	110	3,000	6,000	16	60	219	49

# Blueprint

