



## X-Line lever hoist

### Product information



The Rema® X-Line lever hoist for safe and reliable operation during hoisting, pulling, tensioning or lashing.

#### Properties

- Low effort at full load.
- Increased operational safety due to double pawl system.
- Brake with asbestos free friction discs.
- Freewheel in unloaded condition.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).

#### Standard delivery

- 1,5 m lifting height (max distance between top and bottom hook).

#### Option

- Available in other lifting heights.



**Marking:** According to standard, CE-marked

**Standard:** EN 818-7, EN 13157

Part Code	GTIN No.	WLL ton	Lifting height m	Model	Load Chain dia x pitch mm	Max. hand force on crank kg	Chain falls	Construction height mm	A	B	C	D	E	F	H	Weight kg	Delivery time
-----------	----------	------------	---------------------	-------	------------------------------	--------------------------------	-------------	---------------------------	---	---	---	---	---	---	---	--------------	---------------

R0270000	8717365112515	0.25	-	X-LH025/250KG	4.0 x 12.0	28.2	1	235	100	70	86	163	20	31	235	2.5	30
R0270000-1.5	8717365112522	0.25	1.5	X-LH/250KG/1,5M	4.0 x 12.0	28.2	1	235	100	70	86	163	20	31	235	2.5	3
R0270000-3	8717365112485	0.25	3	X-LH/250KG/3M	4.0 x 12.0	28.2	1	235	100	70	86	163	20	31	235	3.1	3
R0270000-4.5	8717365112492	0.25	4.5	X-LH/250KG/4,5M	4.0 x 12.0	28.2	1	235	100	70	86	163	20	31	235	3.7	3
R0270000-6	8717365112508	0.25	6	X-LH/250KG/6M	4.0 x 12.0	28.2	1	235	100	70	86	163	20	31	235	4.3	3
R0270001	8717365088575	0.5	-	X-LH050/500KG	5.0 x 15.0	24.8	1	310	150	90	118	253	22	32	310	5.5	30
R0270001-1.5	8717365096358	0.5	1.5	X-LH/500KG/1,5M	5.0 x 15.0	24.8	1	310	150	90	118	253	22	32	310	5.5	3
R0270001-3	8717365096860	0.5	3	X-LH/500KG/3M	5.0 x 15.0	24.8	1	310	150	90	118	253	22	32	310	6.4	3
R0270001-4.5	8717365096877	0.5	4.5	X-LH/500KG/4,5M	5.0 x 15.0	24.8	1	310	150	90	118	253	22	32	310	7.3	3
R0270001-6	8717365096884	0.5	6	X-LH/500KG/6M	5.0 x 15.0	24.8	1	310	150	90	118	253	22	32	310	8.2	3
R0270003	8717365088582	0.8	-	X-LH080/800KG	5.6 x 17.0	26.5	1	340	158	98	132	273	26	36	340	7.15	30
R0270003-1.5	8717365096365	0.8	1.5	X-LH/800KG/1,5M	5.6 x 17.0	26.5	1	340	158	98	132	273	26	36	340	7.15	3
R0270003-3	8717365096891	0.8	3	X-LH/800KG/3M	5.6 x 17.0	26.5	1	340	158	98	132	273	26	36	340	8.2	3
R0270003-4.5	8717365096907	0.8	4.5	X-LH/800KG/4,5M	5.6 x 17.0	26.5	1	340	158	98	132	273	26	36	340	9.3	3
R0270003-6	8717365096914	0.8	6	X-LH/800KG/6M	5.6 x 17.0	26.5	1	340	158	98	132	273	26	36	340	10.4	3
R0270005	8717365088599	1.6	-	X-LH16/1600KG	7.1 x 21.0	29.5	1	400	185	111	145	378	29	43	400	10.2	30
R0270005-1.5	8717365096372	1.6	1.5	X-LH/1600KG/1,5M	7.1 x 21.0	29.5	1	400	185	111	145	378	29	43	400	10.2	3
R0270005-3	8717365096921	1.6	3	X-LH/1600KG/3M	7.1 x 21.0	29.5	1	400	185	111	145	378	29	43	400	12	3
R0270005-4.5	8717365096938	1.6	4.5	X-LH/1600KG/4,5M	7.1 x 21.0	29.5	1	400	185	111	145	378	29	43	400	13.8	3
R0270005-6	8717365096945	1.6	6	X-LH/1600KG/6M	7.1 x 21.0	29.5	1	400	185	111	145	378	29	43	400	15.6	3
R0270007	8717365088605	3.2	-	X-LH32/3200KG	10.0 x 28.0	33.5	1	520	212	124	198	418	37	50	520	22	30
R0270007-1.5	8717365096389	3.2	1.5	X-LH/3200KG/1,5M	10.0 x 28.0	33.5	1	520	212	124	198	418	37	50	520	22	3
R0270007-3	8717365096952	3.2	3	X-LH/3200KG/3M	10.0 x 28.0	33.5	1	520	212	124	198	418	37	50	520	25.5	3

R0270007-4.5	8717365096969	3.2	4.5	X-LH/3200KG/4,5M	10.0 x 28.0	33.5	1	520	212 124 198 418 37 50 520 29	3
R0270007-6	8717365096976	3.2	6	X-LH/3200KG/6M	10.0 x 28.0	33.5	1	520	212 124 198 418 37 50 520 32.5	3
R0270009	8717365088612	6.3	-	X-LH63/6300KG	10.0 x 28.0	37	2	640	212 124 230 418 43 53 640 34	30
R0270009-1.5	8717365096396	6.3	1.5	X-LH/6300KG/1,5M	10.0 x 28.0	37	2	640	212 124 230 418 43 53 640 34	3
R0270009-3	8717365096983	6.3	3	X-LH/6300KG/3M	10.0 x 28.0	37	2	640	212 124 230 418 43 53 640 41	3
R0270009-4.5	8717365096990	6.3	4.5	X-LH/6300KG/4,5M	10.0 x 28.0	37	2	640	212 124 230 418 43 53 640 48	3
R0270009-6	8717365097003	6.3	6	X-LH/6300KG/6M	10.0 x 28.0	37	2	640	212 124 230 418 43 53 640 55	3
R0270011	8717365088629	9	-	X-LH90/9000KG	10.0 x 28.0	42	3	730	212 124 338 418 44 67 730 45	30
R0270011-1.5	8717365096402	9	1.5	X-LH/9000KG/1,5M	10.0 x 28.0	42	3	730	212 124 338 418 44 67 730 45	3
R0270011-3	8717365097010	9	3	X-LH/9000KG/3M	10.0 x 28.0	42	3	730	212 124 338 418 44 67 730 56	3
R0270011-4.5	8717365097027	9	4.5	X-LH/9000KG/4,5M	10.0 x 28.0	42	3	730	212 124 338 418 44 67 730 67	3
R0270011-6	8717365097034	9	6	X-LH/9000KG/6M	10.0 x 28.0	42	3	730	212 124 338 418 44 67 730 78	3

# Blueprint

