



## YA mini lever hoist

### Product information



The Rema® YA lever hoist is an extremely robust lever hoist for hoisting, pulling, tensioning and lashing in all directions. With one simple action the lever hoist can be set in its freewheel.

#### Properties

- Very low self weight, compact dimensions.
- The rotatable top and bottom hook are provided with safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Self locked brake that holds the load at any desired height.
- Freewheel is possible in unloaded condition.
- Freewheel by one simple action.
- The hoist is fitted with a rubber anti-slip handle.
- Galvanized load chain (Grade 10).

#### Standard delivery

- 1,5 m lifting height (max distance between top and bottom hookpositions).

#### Option

- Available in other lifting heights.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-7, EN 13157

Part Code	GTIN No.	WLL kg	Lifting height m	Model	Load Chain dia x pitch mm	Max. hand force on crank kg	Chain falls	Construction height mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg	Delivery time
R0208000-1.5M	8717365259999	250	1.5	YA-250KG-1.5M	4.0 x 12	30	1	235	91	70	60	155	19	31	235	2.3	3
R0208000-3M	8717365264979	250	3	YA-250KG-3M	4.0 x 12	30	1	235	91	70	60	155	19	31	235	2.5	3
R0208000-4.5	8717365264610	250	4.5	YA-250KG-4,5M	4.0 x 12	30	1	235	91	70	60	155	19	31	235	2.8	3
R0208000-6	8717365264627	250	6	YA-250KG-6M	4.0 x 12	30	1	235	91	70	60	155	19	31	235	3	3

## Blueprint

