



REMA SELECT 30S adjustable trolley

Product information



The Rema Select 30 S spindle push trolley is suitable for various steel profiles. They are simple, quick and safe to install, ideal for assembly work.

Properties

- Suitable for flat or bevel profiles.
- Equipped with solid steel wheels with maintenance-free bearings.
- Compact and light weight.
- Quick assembly through threaded adjustable.
- Safe by extra locking lever.
- With wheel rupture supports.
- Robust steel version with a low own weight.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL kg	Beam width mm	Model	Minimum radius mm	A mm	Bmin	Bmax	C mm	D mm	E mm	G mm	Weight kg	Delivery time
R0918001	8717365002915	500	64-203	S30S-005	1,100	174	263	324	105	16	25.4	340	6	3
R0918003	8717365002922	1,000	64-203	S30S-010	1,100	174	263	324	105	16	25.4	340	7	3
R0918005	8717365002939	2,000	76-203	S30S-020	1,300	280	339	387	111	22	25.4	340	20	3
R0918007	8717365002946	3,000	76-203	S30S-030	1,400	345	374	438	127	27	26	345	32	3
R0918009	8717365002953	5,000	100-305	S30S-050	1,500	395	450	528	135	35	81	465	53	3

Blueprint

