



## S-3 Webbing slings with triangles

### Product information



This professional webbing sling is extremely suitable for intensive industrial use.

#### Properties

- Duplex version; double band layer.
- WLL stripes, each stripe is 1 ton.
- Every 30 mm band width is 1 ton load capacity.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1, EN 1492-1

**Note:** Packed in plastic including REMA manual.

Part Code	WLL ton
R1213031	1
R1213035	1
R1213037	1
R1213039	1
R1213041	1
R1213043	1
R1213045	1

R1213047	1
R1213049	1
R1213051	1
R1213061	2
R1213065	2
R1213067	2
R1213069	2
R1213071	2
R1213073	2
R1213075	2
R1213077	2
R1213079	2
R1213081	2
R1213091	3
R1213095	3
R1213097	3
R1213099	3
R1213101	3
R1213103	3
R1213105	3
R1213107	3
R1213109	3
R1213111	3

R1213125	4
R1213127	4
R1213129	4
R1213131	4
R1213133	4
R1213135	4
R1213137	4
R1213139	4
R1213141	4
R1213155	5
R1213157	5
R1213159	5
R1213161	5
R1213163	5
R1213165	5
R1213167	5
R1213169	5
R1213171	5