



REMA 212/212BF Geared trolley

Product information



Suitable for various profiles, both for flat or bevel flange.

Properties

- Suitable for flat or bevel flange
- Adjustable flange width by adding or removing rings.
- Solid steel wheels, bearing of maintenance-free ball bearings.
- Short construction height in combination with REMA Select 200 OD hoist 0.5 / 1.0 / 2.0T, by link that replaces the upper hook.
- Wheel rupture supports and anti-surge protection ensure optimum safety.
- 211 type, standard version.
- 211BF type, wide flange version.
- Galvanised hand chain 5 x 23,7 mm.

Standard delivery

- 3 meter operating height.

Option

- Longer or shorter operating chain.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL kg	Beam width mm mm	Model	Minimum radius mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	S mm	Weight kg	Delivery time
R0925001	8717365260322	500	50-135	212-0.5T-50-135	800	205	198	150	55	30	1,5-3	28	8	111	28	239	27	8	3
R0925101	8717365262043	500	130-215	212BF-0.5T-130-215MM	800	205	278	150	55	30	1,5-3	28	8	111	28	239	27	8	3
R0925102	8717365262050	500	215-300	212BF-0.5T-215-300MM	800	205	363	150	55	30	1,5-3	28	8	111	28	239	27	8	3
R0925003	8717365260339	1,000	55-140	212-1.0T-55-140	1,000	242	211	174	68	30	1,5-3	32	10	118	32	254	28	12.4	3
R0925201	8717365262067	1,000	140-215	212BF-1.0T-140-215MM	1,000	242	286	174	68	30	1,5-3	32	10	118	32	254	28	12.4	3
R0925202	8717365262074	1,000	215-300	212BF-1.0T-215-300MM	1,000	242	371	174	68	30	1,5-3	32	10	118	32	254	28	12.4	3
R0925005	8717365260346	2,000	65-155	212-2.0T-65-155	1,100	270	238	194	80	49	1,5-3	40	12	147	36	277	27	18.1	3
R0925301	8717365262081	2,000	150-230	212BF-2.0T-150-230MM	1,100	270	313	194	80	49	1,5-3	40	12	147	36	277	27	18.1	3
R0925302	8717365262098	2,000	230-300	212BF-2.0T-230-300MM	1,100	270	383	194	80	49	1,5-3	40	12	147	36	277	27	18.1	3
R0925007	8717365260353	3,000	90-160	212-3.0T-90-160	1,300	325	246	234	100	60	1,5-3	49	14	177	44	287	29	30.3	3
R0925401	8717365262104	3,000	160-230	212BF-3.0T-160-230MM	1,300	325	316	234	100	60	1,5-3	49	14	177	44	287	29	30.3	3
R0925402	8717365262111	3,000	230-300	212BF-3.0T-230-300MM	1,300	325	386	234	100	60	1,5-3	49	14	177	44	287	29	30.3	3
R0925009	8717365260360	5,000	90-180	212-5.0T-90-180	1,500	370	280	267	110	79	1,5-3	59	16	219	55	320	29	46.5	3
R0925501	8717365262128	5,000	180-230	212BF-5.0T-180-230MM	1,500	370	330	267	110	79	1,5-3	59	16	219	55	320	29	46.5	3
R0925502	8717365262135	5,000	230-300	212BF-5.0T-230-300MM	1,500	370	400	267	110	79	1,5-3	59	16	219	55	320	29	46.5	3

Blueprint

