



Dynamometer 05

Product information



Mechanical properties

- Aluminum housing.
- Alloy steel pulling unit.
- Test load 2 x WLL (without losing accuracy).
- Safety factor 5 x WLL.
- International Protection Rating / Ingress Protection: IP65 (EN60529).

Electrical specifications

- Alkaline battery (3 x AA type).
- Battery operating time about 180 hours.

Electronic specifications

- Operating temperature range between -5° C to + 55° C.
- Accuracy up to approx. 0.1% of the reading value.
- Battery indicator.

Option

- U-13 Unilock bow shackle (2635013).

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155, EN 13889

Note: Includes plastic case, manual and calibration report.

Safety factor: 5

| Part Code | GTIN No. | WLL ton | Model | Shackle | Resolution kg | A mm | B mm | C mm | D mm | E mm | F mm | Weight kg | Delivery time |
|-----------|---------------|---------|------------|----------|---------------|------|------|------|------|------|------|-----------|---------------|
| R1514001 | 8717365111983 | 0.6 | DSD05-0.6T | U-13 ex. | 0.2 | 170 | 16 | 21 | - | - | - | 2.3 | 3 |
| R1514003 | 8717365111990 | 1 | DSD05-1.0T | U-13 ex. | 0.5 | 170 | 16 | 21 | - | - | - | 2.3 | 3 |

Blueprint

