



C811X



C812X

C811X/C812X Lifting point

Product information



Type description

- Type C811 has a safety coefficient 5 in all loading directions.
- Type C812 has a safety coefficient 4 in all loading directions.

Marking: According to standard, CE-marked

Standard: EN 1677-1

Note: Rotatable through 360°, foldable 90°.

Warning: Not rotatable under load.

Safety factor: 4

Part Code	GTIN No.	WLL ton	Thread mm	Model	A mm	B mm	C mm	E mm	F mm	G mm	H mm	M mm	L mm	SW mm	SWI mm	Weight kg	Delivery time
R2611308	8717365176135	0.3	M8	C811X-M8x12-0.3T	33,5	56	30	40	14	28	99	M8	12	13	5	0.38	3
R2611310	8717365176142	0.6	M10	C811X-M10x15-0.6T	34,5	56	30	40	14	28	99	M10	15	17	6	0.38	3
R2611312	8717365176159	1	M12	C811X-M12x18-1.0T	35,5	56	30	40	14	28	99	M12	18	19	7	0.38	3
R2611314	8717365176166	1.3	M14	C811X-M14x21-1.3T	46	74,5	47	55	18	38	135,5	M14	21	22	7	1.3	3
R2611316	8717365176173	1.6	M16	C811X-M16x25-1.6T	46,5	74,5	47	55	18	38	135,5	M16	25	24	10	1.3	30
R2611318	8717365176180	2	M18	C811X-M18x27-2.0T	47	74,5	47	55	18	38	135,5	M18	27	27	10	1.3	3
R2611320	8717365176197	2.5	M20	C811X-M20x30-2.5T	43	79	45	55	25	38	138	M20	30	24	10	1.3	3
R2611322	8717365176203	3	M22	C811X-M22x33-3.0T	63,5	106	62	84	25	56	198,5	M22	33	32	12	4	3
R2611324	8717365176210	4	M24	C811X-M24x36-4.0T	64,5	106	62	84	25	56	198,5	M24	36	36	14	4	3
R2611327	8717365176227	5	M27	C811X-M27x40-5.0T	66,5	106	62	84	25	56	198,5	M27	40	41	14	4	3
R2611330	8717365176234	6.3	M30	C811X-M30x45-6.3T	68	106	62	84	25	56	198,5	M30	45	46	17	4	3
R2611336	8717365176241	10	M36	C812X-M36x54-10T	80	150	76,5	108	32	85	220	M36	54	-	17	6	3
R2611342	8717365176258	12.5	M42	C812X-M42x63-12.5T	80	150	76,5	108	32	85	220	M42	63	-	17	6	3
R2611348	8717365176265	17	M48	C812X-M48x68-17T	90	176	95	128	39	100	257	M48	68	-	17	10.5	3
R2611356	8717365176272	25	M56	C812X-M56x78-25T	90	176	95	126	39	100	257	M56	78	-	17	16.3	3
R2611364	8717365176289	35	M64	C812X-M64x90-35T	105	200	110	126	46	113	277	M64	90	-	19	16.3	3

Blueprint

