



Superclamp S serial

Product information



Adjustable spindle beam clamp for establishing a semi-permanent suspension point when loading at an angle.

Properties

- Compact design and low tare weight.
- Easy mounting.

Marking: According to standard, CE-marked

Standard: EN 13157, EN 12100

| Part Code | GTIN No. | WLL ton | Beam width mm mm | Jaw width mm | Model | A mm | B mm | C mm | D mm | E mm | G mm | H mm | J mm | K mm | Weight kg | Delivery time |
|-----------|---------------|---------|------------------|--------------|-------|------|------|------|-------|------|------|------|------|------|-----------|---------------|
| R3502001 | 8717365016721 | 2 | 76-190 | | S1* | 125 | 3 | 22 | 90 | 188 | 275 | 20 | 77 | 250 | 4 | 3 |
| R3502003 | 8717365016738 | 3 | 76-190 | | S2* | 125 | 6 | 22 | 90 | 188 | 275 | 20 | 77 | 250 | 5.1 | 3 |
| R3502005 | 8717365016745 | 3 | 76-190 | | S2A* | 130 | 12.5 | 22 | 102 | 250 | 275 | 20 | 103 | 268 | 7.4 | 3 |
| R3502007 | 8717365016752 | 4 | 150-254 | | S3* | 130 | 10 | 22 | 112 | 327 | 410 | 25 | 98 | 332 | 10.4 | 3 |
| R3502009 | 8717365016769 | 5 | 76-190 | | S3X | 130 | 12.5 | 22 | 116 | 237 | 295 | 25 | 110 | 300 | 9 | 3 |
| R3502011 | 8717365016776 | 5 | 150-305 | | S3A* | 140 | 12.5 | 32 | 116 | 373 | 410 | 25 | 110 | 360 | 14.9 | 3 |
| R3502013 | 8717365016790 | 6 | 203-457 | | S4S | 140 | 12.5 | 42 | 116 | 498 | 560 | 25 | 110 | 459 | 18.8 | 3 |
| R3502012 | 8717365016783 | 7 | 101-228 | | S4 | 140 | 12.5 | 42 | 118 | 323 | 410 | 32 | 120 | 382 | 17.5 | 3 |
| R3502015 | 8717365016806 | 10 | 203-457 | | S4A | 140 | 20 | 42 | 118 | 498 | 560 | 32 | 112 | 476 | 27.3 | 3 |
| R3502017 | 8717365016813 | 15 | 203-457 | | S12 | 170 | 20 | 50 | 116.5 | 611 | 660 | 40 | 185 | 616 | 53.8 | 3 |
| R3502019 | 8717365016820 | 15 | 406-610 | | S14 | 175 | 20 | 63 | 116.5 | 795 | 810 | 40 | 185 | 673 | 63 | 3 |

Blueprint

