

Portal crane REMA PKA, Aluminum



Product information



Properties

- Very short assembly and disassembly time of a few minutes.
- 3-part dismountable, two columns and a support beam.
- Foldable columns for easy transport.
- Height adjustment, installation in low spaces is possible.
- Adjustable span by one, movable, columns.
- Very low own weight because the crane is made entirely of aluminum and plastic.

Applications

- If a non-permanent lifting point has to be created quickly and easily.
- Ideal for use when changing tools on machines or as an aid for repairs and replacement of parts, machines and pumps.

Standard delivery

- Trolley included.
- Exclusive hoist (see Chapter 1).

Option

- Wall console for 1 side.
- Mobile version (no load).
- Other versions on request.

Material: Aluminium

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157, EN 15011

Part code	GTIN No.	WLL ton	Height m m	Model	Width mm	Main beam length mm	Weight kg	Delivery time
R3940008	8717365023286	1.5	1.18-2.1	PKA-K-2	1,200	2,000	98	3
R3940000	8717365020155	1.5	1.18-2.1	PKA-K-3	1,200	3,000	105	3
R3940009	8717365023293	1.5	1.68-3	PKA-M-2	1,710	2,000	111	3
R3940001	8717365020162	1.5	1.18-2.1	PKA-K-4	1,200	4,000	115	3
R3940002	8717365020179	1.5	1.68-3	PKA-M-3	1,710	3,000	121	3
R3940010	8717365023309	1.5	2.23-4	PKA-G-2	2,290	2,000	127	3
R3940003	8717365020186	1.5	1.68-3	PKA-M-4	1,710	4,000	130	3
R3940004	8717365020193	1.5	2.23-4	PKA-G-3	2,290	3,000	138	3
R3940007	8717365259760	1.5	1.68-3	PKA-M-5	1,710	5,000	140	3
R3940005	8717365020209	1.5	2.23-4	PKA-G-4	2,290	4,000	146	3
R3940006	8717365020308	1.5	2.23-4	PKA-G-5	2,290	5,000	156	3