

HS stationary lifting tables



Product information



The universal stationary lifting table for lifting heavy loads can be used in a space-saving manner by placing the lifting table in a pit.

Properties

- Robust support construction.
- Profile reinforced table.
- Solid steel scissors.
- This lifting table is equipped with an aluminium safety frame.
- Support inspection for safe maintenance.
- Overload protection.
- Hose rupture safety valve.
- Hard chromed cylinder and piston rod.
- Lifetime lubricated bearings.
- Operating voltage 400V, control voltage 24V.
- Protection class IP54.

Standard delivery

- Includes 24 V push button switch with emergency stop.
- Removable lifting eyes for easy transport.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 1570

| Part Code | GTIN No. | WLL ton | Model | Lifting times | Motor power kW | Lifting cycle/hour | A mm | B mm | C mm | D mm | E mm | H mm | Weight kg | Delivery time |
|-----------|---------------|---------|---------|---------------|----------------|--------------------|------|-------|-------|------|-------|-------|-----------|---------------|
| R3459005 | 8717365021534 | 0.5 | HS05-01 | 25 | 1.1 | 21 | 243 | 2,000 | 800 | 680 | 1,615 | 1,043 | 193 | 3 |
| R3459001 | 8717365016257 | 1 | HS1-01 | 20 | 0.75 | 21 | 248 | 1,300 | 820 | 640 | 1,240 | 1,033 | 160 | 3 |
| R3459007 | 8717365021824 | 1 | HS1-04 | 30 | 1.1 | 15 | 283 | 1,700 | 1,000 | 640 | 1,580 | 1,343 | 210 | 3 |
| R3459002 | 8717365016264 | 2 | HS2-01 | 20 | 1.5 | 21 | 273 | 1,300 | 850 | 785 | 1,220 | 1,043 | 235 | 3 |
| R3459003 | 8717365021817 | 2 | HS2-06 | 35 | 2.2 | 15 | 293 | 2,000 | 1,000 | 785 | 1,600 | 1,343 | 375 | 3 |
| R3459004 | 8717365016271 | 4 | HS4-01 | 40 | 2.2 | 13 | 288 | 1,700 | 1,200 | 900 | 1,600 | 1,098 | 375 | 3 |
| R3459006 | 8717365021541 | 4 | HS4-06 | 45 | 2.2 | 10 | 348 | 2,200 | 1,200 | 900 | 2,000 | 1,448 | 505 | 3 |

Blueprint

