

## RWL worm gear winch with freewheel system



### Product information



#### Properties

- Braked design.
- Crank gradually adjustable in length.
- Drum and shafts provided with bearings.
- Freewheel, through protected pawl system.
- Powdercoating RAL2004.

#### Standard delivery

- Does not include wire rope.

#### Option

- Steel wire rope on request and hook with safety latch.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 13157

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Gear ratio	Max. reel capacity mm	Length handle mm	Load capacity last layer kg	load capacity 1st layer kg	Weight kg	Delivery time
R2018001	8717365259296	0.25	RWL-250	5	15:1	20	250/100	75	250	11	3
R2018003	8717365259302	0.5	RWL-500	6	24:1	30	250/100	300	500	17	3
R2018005	8717365259319	1	RWL-1000	10	26:1	35	350/100	550	1,000	36	3

## Technical data

Model	A	B	C	D	F	G	H	J	K	L	M	N	Q	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
RWL-250	167	332	150	202	137	100	26	13	118	11	89	80	99	24.5
RWL-500	195	367												

## Blueprint

