



Super Shackle no 858, Gunnebo with safety Bolt

Product information

Bow shackle with safety bolt.

Material: High tensile steel, quenched and tempered

Marking: According to standard, CE-marked, WLL

Temperature range: -20°C up to 200°C

Finish: All parts hot dip galvanized + brown colour marking

Standard: US. FED. SPEC. RR-C-271

Safety factor: 5:1

Grade: 8

| Part Code | WLL ton | a mm | c mm | d mm | d1 mm | d2 mm | e mm | Weight kg | Delivery time |
|--------------|------------|---------|---------|-------------|----------|----------|---------|--------------|---------------|
| 420100330480 | 3.3 | 21 | 51 | 1/2" - 13 | 16 | 33 | 33 | 0.4 | 30 |
| 420100500480 | 5 | 27 | 60 | 5/8" - 16 | 19 | 40 | 42 | 0.7 | 30 |
| 420100700480 | 7 | 31 | 71 | 3/4" - 19 | 22 | 48 | 49 | 1.2 | 30 |
| 420100950480 | 9.5 | 37 | 84 | 7/8" - 22 | 25 | 52 | 60 | 1.7 | 30 |
| 420101250480 | 12.5 | 43 | 95 | 1" - 25 | 28 | 60 | 68 | 2.5 | 30 |
| 420101500480 | 15 | 46 | 108 | 1 1/8" - 28 | 32 | 64 | 74 | 3.4 | 30 |
| 420101800480 | 18 | 52 | 119 | 1 1/4" - 32 | 35 | 72 | 83 | 4.8 | 30 |
| 420102100480 | 21 | 57 | 132 | 1 3/8" - 35 | 38 | 76 | 89 | 7 | 30 |
| 420103000480 | 30 | 60 | 146 | 1 1/2" - 38 | 42 | 84 | 98 | 8.8 | 30 |
| 420104000480 | 40 | 74 | 178 | 1 3/4" - 45 | 50 | 105 | 127 | 15 | 30 |
| 420112000480 | 120 | 127 | 330 | 3 1/4" - 83 | 83 | 171 | 190 | 70 | 30 |

Blueprint

