



Beam Clamp - IPTK

Product information

General:

This IPTK series beam clamp is suitable for use as a temporary tackle eye for horizontal lifting and transportation of steel (H) beams, profiles and structures. Can also be used as upside down attached (temporary) lifting point.

Features:

- Available in capacities of 2 thru 25 metric tons.
- Wide variety of jaw openings available: 75 to 1020 mm".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Steel.

Marking: According to standard, CE-marked

Standard: EN 13155

| Part Code | WLL ton | Jaw width mm | Model | Weight kg | Delivery time |
|-----------------|---------|--------------|---------|-----------|---------------|
| 502100201900230 | 2 | 75-190 | 2-IPTK | 6 | 30 |
| 502100301900230 | 3 | 75-190 | 3-IPTK | 6.5 | 30 |
| 502100402800230 | 4 | 150-280 | 4-IPTK | 8.5 | 30 |
| 502100503500230 | 5 | 120-350 | 5-IPTK | 11 | 30 |
| 502102501020230 | 25 | 450-1,020 | 25-IPTK | 225 | 30 |

Blueprint

