



Beam Clamp - IPBSNZ

Product information

General:

The IPBSNZ beam clamp is used for lifting, transferring and stacking. Offset hoisting eye allows for level lifts of I-Beams. Also for lifting fabrications and ship sections. This series of clamps can be used in vertical and horizontal moving, transferring and stacking of different types of structural designs, such as I-Beams, depending on the application desired.

Features:

- Available in capacities of 1.5 thru 4.5 metric tons
- Wide variety of jaw openings available: 0 to 50mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Warning: For a correct operation of the clamp a minimal load of 10% of the WLL is needed.

Part Code	WLL ton	Jaw width mm	Model	Weight kg	Delivery time
502100150320190	1.5	0-32	1.5-IPBSNZ	14	30
502100300400190	3	0-40	3-IPBSNZ	22	30
502100450500190	4.5	0-50	4.5-IPBSNZ	30.5	30

Blueprint

