



Welded Master Link Crosby A-347

Product information

Master link with large inner diameter and length.

These rings with auxiliaries have the dimensions that allow the manufacture of steel wire ropes slings with 3 or 4 legs.

Material: Alloy steel — Quenched & Tempered

Marking: According to standard, Manufacturers name, traceability code.

Standard: EN 1677-4

Safety factor: 5:1

Grade: 8

Part Code	Chain diameter mm	WLL ton	Chain Ø inch	Chain G80 3 and 4 legs	Chain G100 3 and 4 legs	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg	Delivery time
401100240150	12-13	2.4	1/2	-	-	13	60	120	12	85	45	6.5	0.81	30
401100410150	13-17	4.1	11/16	6-7	6	17	90	160	13	120	60	6.5	1.6	30
401100420150	13-19	4.2	3/4	7	6-7	19	90	160	13	120	60	6.5	1.8	30
401100580150	16-22	5.8	7/8	-	-	22	145	275	16	120	60	8.5	3.53	30
401100670150	17-22	6.7	7/8	-	-	22	100	180	17	160	90	8.5	3.35	30
401100850150	20-22	8.5	7/8	-	-	22	90	170	20	150	80	8.5	3.93	30
401100890150	19-25	8.9	1	10	10	25	145	275	19	160	90	8.5	5.3	30
401101070150	20-25	10.7	1	-	-	25	100	190	20	150	80	8.5	4.65	30
401101290150	22-28	12.9	1-1/8	-	-	28	110	210	22	170	90	10.5	6.4	30
401101450150	22-28	14.5	1-1/8	13	13	28	145	275	22	180	100	10.5	7.2	30
401101700150	25-31	17	1-7/32	16	13	32	145	275	25	210	115	13.5	9.9	30
401101700151	25-32	17	1-1/4	-	-	32	140	270	25	190	100	13.5	9.92	30
401102810150	32-38	28.1	1-1/2	-	-	38	140	270	32	270	140	16.7	18.23	30
401102810151	31-40	28.1	1-9/16	-	-	40	160	300	31	275	145	16.7	18.68	30
401103830150	36-45	38.3	1-3/4	22	19-20	45	180	340	36	285	155	-	26.7	30
401103830151	38-45	38.3	1-3/4	-	-	45	170	320	38	270	140	-	27.96	30
401104500150	38-50	45	2	-	-	50	200	380	38	270	140	-	32.86	30
401104500150	45-51	45	2	-	-	51	190	350	45	340	180	-	42.92	30
401106700150	50-57	67	2-1/4	-	-	57	203	406	50	380	200	-	59.7	30

Blueprint

