



Welded Master Link Crosby A-347

Product information

Master link with large inner diameter and length.

These rings with auxiliaries have the dimensions that allow the manufacture of steel wire ropes slings with 3 or 4 legs.

Material: Alloy steel — Quenched & Tempered

Marking: According to standard, Manufacturers name, traceability code.

Standard: EN 1677-4

Safety factor: 5:1

Grade: 8

| Part Code | Chain diameter mm | WLL ton | Chain Ø inch | Chain G80 3 and 4 legs | Chain G100 3 and 4 legs | A mm | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg | Delivery time |
|--------------|-------------------|---------|--------------|------------------------|-------------------------|------|------|------|------|------|------|------|-----------|---------------|
| 401100240150 | 12-13 | 2.4 | 1/2 | - | - | 13 | 60 | 120 | 12 | 85 | 45 | 6.5 | 0.81 | 30 |
| 401100410150 | 13-17 | 4.1 | 11/16 | 6-7 | 6 | 17 | 90 | 160 | 13 | 120 | 60 | 6.5 | 1.6 | 30 |
| 401100420150 | 13-19 | 4.2 | 3/4 | 7 | 6-7 | 19 | 90 | 160 | 13 | 120 | 60 | 6.5 | 1.8 | 30 |
| 401100580150 | 16-22 | 5.8 | 7/8 | - | - | 22 | 145 | 275 | 16 | 120 | 60 | 8.5 | 3.53 | 30 |
| 401100670150 | 17-22 | 6.7 | 7/8 | - | - | 22 | 100 | 180 | 17 | 160 | 90 | 8.5 | 3.35 | 30 |
| 401100850150 | 20-22 | 8.5 | 7/8 | - | - | 22 | 90 | 170 | 20 | 150 | 80 | 8.5 | 3.93 | 30 |
| 401100890150 | 19-25 | 8.9 | 1 | 10 | 10 | 25 | 145 | 275 | 19 | 160 | 90 | 8.5 | 5.3 | 30 |
| 401101070150 | 20-25 | 10.7 | 1 | - | - | 25 | 100 | 190 | 20 | 150 | 80 | 8.5 | 4.65 | 30 |
| 401101290150 | 22-28 | 12.9 | 1-1/8 | - | - | 28 | 110 | 210 | 22 | 170 | 90 | 10.5 | 6.4 | 30 |
| 401101450150 | 22-28 | 14.5 | 1-1/8 | 13 | 13 | 28 | 145 | 275 | 22 | 180 | 100 | 10.5 | 7.2 | 30 |
| 401101700150 | 25-31 | 17 | 1-7/32 | 16 | 13 | 32 | 145 | 275 | 25 | 210 | 115 | 13.5 | 9.9 | 30 |
| 401101700151 | 25-32 | 17 | 1-1/4 | - | - | 32 | 140 | 270 | 25 | 190 | 100 | 13.5 | 9.92 | 30 |
| 401102810150 | 32-38 | 28.1 | 1-1/2 | - | - | 38 | 140 | 270 | 32 | 270 | 140 | 16.7 | 18.23 | 30 |
| 401102810151 | 31-40 | 28.1 | 1-9/16 | - | - | 40 | 160 | 300 | 31 | 275 | 145 | 16.7 | 18.68 | 30 |
| 401103830150 | 36-45 | 38.3 | 1-3/4 | 22 | 19-20 | 45 | 180 | 340 | 36 | 285 | 155 | - | 26.7 | 30 |
| 401103830151 | 38-45 | 38.3 | 1-3/4 | - | - | 45 | 170 | 320 | 38 | 270 | 140 | - | 27.96 | 30 |
| 401104500150 | 38-50 | 45 | 2 | - | - | 50 | 200 | 380 | 38 | 270 | 140 | - | 32.86 | 30 |
| 401104500150 | 45-51 | 45 | 2 | - | - | 51 | 190 | 350 | 45 | 340 | 180 | - | 42.92 | 30 |
| 401106700150 | 50-57 | 67 | 2-1/4 | - | - | 57 | 203 | 406 | 50 | 380 | 200 | - | 59.7 | 30 |

Blueprint

