



Chain Block POWERTEX Blackline PCB-S2

Product information

POWERTEX



Chain Block POWERTEX Blackline PCB-S2 is a hoist of high quality which is durable and easy to operate using the ergonomic hand chain. The hoist is powder coated in matt black, and mounted with a black chain, which makes it perfect for use on stages and in the amusement industry.

The hoist is in a compact, lightweight construction.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

Option:

- Chain bag

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C

Finish: Powder coated body in matt black and plated frame components

Standard: EN 13157, EN 818-7

Safety factor: 4:1

| Part Code | WLL ton | Lifting height m | Model | Load chain mm | Hand chain mm | Number of falls | Hand force max. kg | A mm | B mm | C mm | D mm | H min mm | Weight kg | Delivery time |
|-----------------|---------|------------------|-----------------|---------------|---------------|-----------------|--------------------|------|------|------|------|----------|-----------|---------------|
| 500100050300220 | 0.5 | 3 | PCB-S2BK/500KG | 5,0 x 15,0 | 5,0 x 23,7 | 1 | 21.5 | 130 | 128 | 22 | 34 | 280 | 8.9 | 30 |
| 500100050600220 | 0.5 | 6 | PCB-S2BK/500KG | 5,0 x 15,0 | 5,0 x 23,7 | 1 | 21.5 | 130 | 128 | 22 | 34 | 280 | 9.8 | 30 |
| 500100100300220 | 1 | 3 | PCB-S2BK/1000KG | 6,3 x 19,0 | 5,0 x 23,7 | 1 | 29.1 | 150 | 145 | 26 | 39 | 330 | 11.7 | 30 |
| 500100100600220 | 1 | 6 | PCB-S2BK/1000KG | 6,3 x 19,0 | 5,0 x 23,7 | 1 | 29.1 | 150 | 145 | 26 | 39 | 330 | 12 | 30 |

Blueprint

