

Open Body Turnbuckles Oval Eye - Oval Eye

Product information



General:

- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Testing on request.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals or over 5x WLL

Part Code	WLL ton	Thread dia. X Take-up mm	L min. mm	L max. mm	A mm	J mm	K mm	L mm	Weight kg	Delivery time
422100230240	0.23	6.35 x 102	198	300	121	6	9	20	0.12	30
422100360240	0.36	7.94 x 114	230	344	138	8	11	24	0.2	30
422100540240	0.54	9.53 x 152	291	444	181	9	13	28	0.34	30
422100100240	1	12.7 x 152	332	510	191	11	18	37	0.7	30
422100100245	1	12.7 x 229	409	614	266	11	18	37	0.77	30
422100100246	1	12.7 x 305	485	815	343	11	18	37	0.97	30
422100160245	1.59	15.9 x 229	450	655	276	13	22	44	1.32	30
422100160240	1.59	15.9 x 152	373	557	200	13	22	44	1.49	14

422100160246	1.59	15.9 x 305	525	862	353	13	22	44	1.55	30
422100240240	2.36	19.1 x 152	416	607	210	16	25	53	1.72	30
422100240245	2.36	19.1 x 229	492	697	286	16	25	53	1.92	30
422100240246	2.36	19.1 x 305	568	911	362	16	25	53	2.49	30
422100240247	2.36	19.1 x 457	721	1,216	514	16	25	53	3.26	30
422100330240	3.27	22.2 x 305	592	942	370	19	32	60	3.27	14
422100330245	3.27	22.2 x 457	745	1,246	523	19	32	60	4.51	30
422100450245	4.54	25.4 x 152	507	710	228	23	36	76	4.1	30
422100450247	4.54	25.4 x 305	660	1,015	380	23	36	76	5.22	30
422100450246	4.54	25.4 x 457	812	1,320	532	23	36	76	6.35	30
422100450240	4.54	25.4 x 610	964	1,625	685	23	36	76	7.82	30
422100690240	6.89	31.8 x 305	719	1,087	384	29	46	90	8.62	30
422100690245	6.89	31.8 x 457	871	1,392	537	29	46	90	10.4	30
422100690246	6.89	31.8 x 610	1,024	1,697	689	29	46	90	12.2	30
422100970240	9.71	38.1 x 305	775	1,156	400	32	54	103	12.5	30
422100970245	9.71	38.1 x 457	927	1,461	553	32	54	103	14.1	30
422100970246	9.71	38.1 x 610	1,080	1,765	705	32	54	103	17	30
422101270240	12.7	44.5 x 457	1,000	1,457	568	38	60	117	23.8	30
422101270245	12.7	44.5 x 610	1,153	1,762	721	38	60	117	26.3	30
422101680240	16.8	51.0 x 610	1,313	1,923	738	45	68	146	8.7	30
422102720240	27.2	63.5 x 610	1,387	1,997	789	51	79	165	65	30
422103400240	34	70 x 610	1,448	2,057	788	57	82	177	88	30

Blueprint

