



Eye Hook Crosby L-320 CN

Product information

Features:

- Proper design, careful forging and precision controlled quenched and tempering give maximum strength without excessive weight and bulk.
- Hook extra marked with Deformation Indicators – Two strategically placed marks, one below just the shank or eye and the other on the hook tip, which allows for a QUIC-CHECK™ measurement to determine if the throat opening has changed, thus indicating abuse or overload. To check, use a measuring device to measure the distance between the marks. If the measurement does not meet the dimensions shown below (Deformation Indicator AA), the hook should be inspected further for possible damage.
- Hook extra marked with Angle Indicators – Indicates the maximum included angle which is allowed between two (2) sling legs in the hook.
- Also Available in Alloy steel Grade 8.

Replacement Latch Kit S-4320 for 0.75 ton hooks up to 15 ton hooks. Latch Kit PL for 3.2 ton hooks up to 40 ton hooks.

Material: Carbon steel

Marking: According to standard, CE-marked

Standard: EN 1677-5

Safety factor: 5:1

Grade: 6

Part Code	WLL ton	Hook ID Code	C mm	D mm	F mm	G mm	J mm	K mm	M mm	N mm	O mm	Q mm	T mm	AA** mm	Weight kg	Delivery time
400300080010	0.75	D	85	72	31.8	18.5	22.9	16	16	9.14	22.6	19.1	22.1	38.1	0.28	30
400300100010	1	F	97	79	35.1	21.3	23.6	18	18	10.7	23.1	23.1	24.9	50.8	0.4	30
400300160010	1.6	G	105	89.5	38.1	25.4	25.4	22.4	22.4	14	25.4	28.7	26.2	50.8	0.65	30
400300200010	2	H	119	101	41.4	28.7	28.7	23.9	23.8	14.7	27.7	31.8	29.5	50.8	0.94	30
400300300010	3.2	I	147	122	51	36.6	37.3	33.3	33.3	18.3	34.5	39.6	38.9	63.5	1.95	30
400300500010	5	J	187	159	63.5	46	44.5	42.2	42.2	22.9	40.9	51	49.8	76.2	3.76	30
400300750010	7.5	K	230	189	76	57	58	47.8	41.4	28.2	53	62	62.5	102	6.8	30
400301000010	10	L	256	211	82.5	66	63.5	55.5	49.3	32.3	57.5	72	66.5	102	9.42	30
400301500010	15	N	318	262	108	76	84	68.5	60.5	39.6	76.5	89	72	127	17.9	30
400302000010	20	O	357	346	127	92	102	76	76.2	44.5	82.5	89	87.5	165	27.2	30
400302500010	25	P	462	357	137	116	108	95.2	81	51	76	114	98.5	178	47.6	30
400303000010	30	S	511	392	152	129	121	114	82.6	55.4	86	125	121	203	67	30
400304000010	40	T	602	470	178	152	146	140	99.3	64.3	105	145	145	254	103	30

Blueprint

