



Pneumatic vacuum lifters VLA

Product information



For horizontal transport of non-porous, stable and flat sheets of metal, plastic and other materials.

Properties

- VLA types are driven by an pneumatic vacuum pump.

Safety:

- Vacuum protection against release.
- Acoustic signal at negative pressure.
- Safety bar for sufficient distance.
- Pressure gauge, vacuum control.
- Acoustic signal included.
- Rechargeable batteries and charger.
- Minimum air pressure must be 6-7 Bar.

Benefits:

- Ergonomic action by 1 person.
- Low maintenance.

Option

- Manual mechanical rotation and tilting.
- Vacuum lifters for wood and stone on request.
- Higher capacities on request.

IMPORTANT!

- Always check the material specifications and dimensions (L x W x D) of the sheet or workpiece to be lifted.
- Larger tonnages and / or other specifications on request.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155

| Part code | GTIN No. | WLL ton | Model | Suction pads quantity / Size mm | Construction height mm | L x B mm | Weight kg | Delivery time |
|-----------|---------------|------------|------------|------------------------------------|---------------------------|-------------|--------------|---------------|
| R3660013 | 8717365022173 | 0.25 | VLA4F-0.25 | 4 x 250 | 620 | 1750 x 1150 | 55 | 3 |
| R3660015 | 8717365022180 | 0.5 | VLA4F-0.5 | 4 x 300 | 620 | 1750 x 1150 | 55 | 3 |
| R3660017 | 8717365022197 | 0.5 | VLA6F-0.5 | 6 x 250 | 620 | 2200 x 1200 | 90 | 3 |
| R3660019 | 8717365022203 | 1 | VLA6F-1.0 | 6 x 300 | 620 | 2200 x 1200 | 90 | 3 |
| R3660021 | 8717365022210 | 1 | VLA8F-1.0 | 8 x 250 | 620 | 2750 x 1150 | 150 | 3 |
| R3660023 | 8717365022227 | 1.5 | VLA8F-1.5 | 8 x 300 | 620 | 2750 x 1150 | 150 | 3 |