



Shank Hook Crosby S-319BN

Product information

- The most complete line of shank hoist hooks. Available 3/4 to 300 metric tons.
- Proper design, careful forging, and precision controlled quench and tempering give maximum strength without excessive weight and bulk.

Material: Bronze - Quenched and Tempered

Safety factor: 4:1

| Part Code | WLL ton | Hook ID Code | D mm | F mm | G mm | H mm | J mm | K mm | L mm | M mm | O mm | P mm | R mm | T mm | X mm | Y mm | Z mm | AA* mm | O2†† | T2†† | Delivery time |
|--------------|---------|--------------|------|------|------|------|------|------|------|------|-------|------|------|------|------|------|------|--------|------|------|---------------|
| 420500051410 | 0.5 | †D | 72.5 | 31.8 | 18.5 | 20.6 | 23.6 | 16 | 131 | 16 | †23.6 | 49.8 | 59.5 | 24.6 | 15 | 52.5 | 17.5 | 31.8 | - | - | 30 |
| 420500061410 | 0.6 | †F | 80.5 | 35.1 | 21.3 | 23.9 | 24.6 | 18 | 144 | 18 | †24.6 | 56.5 | 66 | 24.6 | 19.3 | 57 | 19.8 | 50.8 | - | - | 30 |
| 420500101410 | 1 | †G | 91 | 38.1 | 25.4 | 29.5 | 26.9 | 22.4 | 161 | 22.4 | †26.9 | 62 | 70 | 26.2 | 18.3 | 66 | 22.4 | 50.8 | - | - | 30 |
| 420500141410 | 1.4 | †H | 102 | 41.1 | 29 | 33.3 | 30.2 | 23.9 | 181 | 23.9 | †29.5 | 70.5 | 80.5 | 29.5 | 22.4 | 72 | 25.4 | 50.8 | - | - | 30 |
| 420500201410 | 2 | †I | 123 | 51 | 36.6 | 41.4 | 38.1 | 33.3 | 219 | 28.7 | †34.5 | 88 | 98 | 38.9 | 29.5 | 87.5 | 31.8 | 63.5 | 25.4 | 38.1 | 30 |
| 420500351410 | 3.5 | †J | 160 | 63.5 | 46.2 | 52.5 | 45.2 | 42.2 | 265 | 36.6 | 40.9 | 117 | 121 | 49.3 | 35.8 | 97.5 | 39.6 | 76.2 | 33.3 | 47.8 | 30 |
| 420500501410 | 5 | †K | 192 | 76 | 57.5 | 67 | 61 | 47.8 | 318 | 41.4 | 53 | 133 | 149 | 62.5 | 46 | 111 | 49.3 | 101 | 46 | 57.2 | 30 |
| 420500651410 | 6.5 | †L | 212 | 82.5 | 66 | 74.5 | 66.5 | 55.5 | 409 | 49.3 | 57.5 | 151 | 162 | 66 | 51 | 178 | 55.5 | 101 | 51 | 58.7 | 30 |
| 420501001410 | 10 | †N | 263 | 108 | 76.5 | 89 | 86.5 | 68.5 | 461 | 60.5 | 76.5 | 175 | 207 | 71.5 | 65 | 178 | 67 | 127 | 69.9 | 65 | 30 |

Blueprint

