

Fixed Lifting Ring HR



Product information



LIFTEUROPE carries male rings up to M64 diameter in stock, with WLL of up to 45 tons on request.

The HR fixed ring is individually packaged, comes with an EC declaration and is readily available. Legible marking is also used to ensure item traceability.

Machinery Directive 2006/42/CE

Material: High strength alloy steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Standard: EN 1677-1

Safety factor: 4:1

Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	Weight kg	Delivery time
4215MALRM6	0.4	25	45	25	10	10	45	14	M6	0.05	14
4215MALRM8	0.8	25	45	25	10	10	45	14	M8	0.06	14
4215MALRM10	1	25	45	25	10	10	45	18	M10	0.11	14
4215MALRM12	1.6	35	63	35	14	13	62	22	M12	0.18	14
4215MALRM14	3	35	63	35	14	14	62	21	M14	0.29	14
4215MALRM16	4	35	63	35	14	13	62	28	M16	0.28	14
4215MALRM18	5	50	90	50	20	20	90	27	M18	0.84	14
4215MALRM20	6	50	90	50	20	20	90	30	M20	0.45	14
4215MALRM24	8	50	90	50	20	20	90	38	M24	0.87	14
4215MALRM27	10	60	108	65	24	24	109	45	M27	1.66	14
4215MALRM30	12	60	108	65	24	25	109	45	M30	1.66	14
4215MALRM36	16	70	126	75	28	30	128	55	M36	2.65	14
4215MALRM42	24	80	144	85	32	35	147	65	M42	4.03	14
4215MALRM48	32	90	166	100	38	40	168	70	M48	6.38	14
4215MALRM56	36	100	184	110	42	38	187	78	M56	8.8	14
4215MALRM64	45	110	206	120	48	42	208	90	M64	12.4	14

Blueprint

