

Fixed Lifting Ring Female HR



Product information



LIFTEUROP has female fixed rings up to M30 diameter with WLL of up to 12 tons.

The HR fixed ring is individually packaged, comes with an EC declaration and is readily available. Legible marking is also used to ensure item traceability.

Machinery Directive 2006/42/CE

Material: High strength alloy steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +100°C

Standard: EN 1677-1

Safety factor: 4:1

Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	M mm	Weight kg	Delivery time
4215FELRM6	0.4	25	45	25	10	10	45	M6	0.05	14
4215FELRM8	0.8	25	45	25	10	10	45	M8	0.05	14
4215FELRM10	1	25	45	25	10	10	45	M10	0.09	14
4215FELRM12	1.6	35	63	35	14	13	62	M12	0.16	14
4215FELRM14	3	35	63	35	14	14	62	M14	0.26	14
4215FELRM16	4	35	63	35	14	13	62	M16	0.24	14
4215FELRM18	5	50	90	50	20	20	90	M18	0.75	14
4215FELRM20	6	50	90	50	20	20	90	M20	0.36	14
4215FELRM24	8	50	90	50	20	20	90	M24	0.72	14
4215FELRM27	10	60	108	65	24	24	109	M27	1.4	14
4215FELRM30	12	60	108	65	24	25	109	M30	1.32	14

Blueprint

