



Regular Swivel G-7713 - Eye/Eye

Product information

The Green Pin® EE Swivel is a swivel with eye-eye end-fittings. The swivel is made from high tensile steel and can be used under water. Galvanization of the Green Pin® EE Swivel ensures its long-term durability. The swivel is available in a range with a working load limit from 0.4 up to 20.5 ton.

Standard: Generally to US Federal Spec. RR-C-271, Type VII, Class 2.

Certification: Test certificates can be supplied upon request.

Material: High tensile steel, quenched and tempered.

Finish: Hot dipped galvanised.

Safety factor: 5:1

| Part Code | WLL ton | EWL mm | A mm | B mm | C mm | D mm | e mm | f mm | g mm | Weight kg | Delivery time |
|------------------|--------------------|-------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|----------------------|----------------------|
| 422500040030 | 0.39 | 75 | 6 | 87 | 32 | 18 | 19 | 27 | 75 | 0.1 | 10 |
| 422500060030 | 0.57 | 90 | 8 | 107 | 41 | 21 | 25 | 32 | 91 | 0.18 | 10 |
| 422500100030 | 1.02 | 109 | 10 | 131 | 51 | 24 | 32 | 38 | 111 | 0.3 | 10 |
| 422500160030 | 1.6 | 138 | 13 | 164 | 64 | 33 | 38 | 51 | 138 | 0.6 | 3 |
| 422500240030 | 2.4 | 167 | 16 | 198 | 76 | 40 | 45 | 61 | 166 | 1.13 | 10 |
| 422500330030 | 3.3 | 183 | 19 | 221 | 89 | 45 | 51 | 67 | 183 | 1.79 | 10 |
| 422500450030 | 4.5 | 213 | 22 | 257 | 102 | 53 | 57 | 78 | 213 | 2.55 | 10 |
| 422500570030 | 5.7 | 245 | 25 | 298 | 114 | 59 | 64 | 86 | 248 | 4.06 | 10 |
| 422500820030 | 8.2 | 273 | 32 | 357 | 143 | 68 | 80 | 68 | 293 | 8.48 | 10 |
| 422502050030 | 20.5 | 425 | 38 | 541 | 198 | 110 | 122 | 110 | 465 | 25.7 | 10 |

Blueprint

