



## Transition Link Pewag BW

### Product information

For pewag welded system.  
Intermediate link or transition link and securing link.

**Material:** High duty grade 10.

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	EWL	For chain Ø in mm 1- + 2-leg BW I/II	d mm	t mm	w mm	s mm	Weight kg	Delivery time
402200100120	BW 7	1	36	5	7	36	16	-	0.03	20
402200140120	BW 8*	1.4	36	6	8	36	16	-	0.05	20
402200190120	BW 9	1.9	44	7	9	44	20	-	0.07	20
402200250120	BW 10	2.5	44	8	10	44	20	-	0.09	20
402200400120	BW 13	4	54	10	13	54	25	10	0.17	3
402200670120	BW 16	6.7	70	13	17	70	34	14	0.39	20
402201000120	BW 20	10	85	16	20	85	40	14	1	20
402201250120	BW 22	12.5	115	-	23	115	50	17	1.16	20
402201400120	BW 23*	14	115	19	27	140	50	20	1.92	20
402201620120	BW 26	16.2	140	-	33	150	70	26	3.16	20
402201900120	BW 27*	19	140	22	36	170	75	-	4.35	20
402202650120	BW 32	26.5	150	26	40	170	80	-	4.12	20
402203100120	BW 36	31	170	-	50	200	100	-	10.58	20
402204040120	BW 40	40.4	170	32	-	170	-	-	-	20
402206400120	BW 50	64	200	-	-	200	-	-	-	20

# Blueprint

