



## Master Link Assembly X-006

### Product information

- Welded Master Link designed for 3-4 legs Chain, Wire Rope and Webbing Slings.
- The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.
- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Manufactured in accordance with EN 1677- 4 and ASME B30.26.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL	EWL	Proof Load	For chain gr 10 Ø 3-4 leg	Can be used up to single hook acc. to DIN 15401 no.	WLL β 0-45°	D	A	B	d	a	b	Weight	Delivery time
		ton	mm	kN	mm		ton	mm	mm	mm	mm	mm	mm	kg	
402100420410	BD-19 + 2 DD+13	4.2	189	103	6	5	4,2	19	135	75	13	54	25	1.3	3
402100820410	BD-22 + 2 DD+16	8.2	230	201	7,8	6	8,2	22	160	90	16	70	34	2.2	3
402101070410	BD-28 + 2 DD+19	10.7	265	262	10	8	10,7	28	180	100	19	85	40	3.9	3
402101570410	BD-32 + 2 DD+22	15.7	315	385	13	10	15,7	32	200	110	22	115	50	6.1	3
402102220410	BD-36 + 2 DD+28	22.2	325	544	16	16	22,2	36	260	140	28	140	65	10.6	3
402104000410	BD-50 + 2 DD+36	40	470	980	22	32	40,0	50	300	200	36	170	75	23.8	3

# Blueprint

