



## Eye Foundry Hook X-047

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Designed for the assembly of chain slings where wide throat openings are necessary

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Standard:** EN 1677-1

**Warning:** Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	EWL mm	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
402300250800	7-8	2.5	123	24	12	30	123	62	19	0.8	3
402300400800	10	4	149	32	15	35	149	74	23	1.6	3
402300670800	13	6.7	180	40	19	39	180	88	32	2.6	30
402301000800	16	10	213	50	25	46	213	98	41	4.5	3
402301600800	20	16	248	60	26	59	248	113	58	9.3	3

## Blueprint

