

## Swivel Self Locking Hook X-027



### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Warning:** This hook is a positioning device and is not intended to rotate under load.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
420500140940	6	1.4	149	32	25	12	19	149	28	15	0.7	30
420500250940	7-8	2.5	186	36	30	13	24	186	34	20	1.2	3
420500400940	10	4	218	41	38	16	30	218	44	26	2	3
420500670940	13	6.7	276	46	48	21	39	276	51	30	4.1	3
420501000940	16	10	329	61	56	23	49	329	60	36	7.2	3
420501600940	20	16	387	74	86	25	65	403	70	53	13	30
420501900940	22	19	457	97	98	33	63	455	80	49	20	3
420502650940	26	26.5	535	123	120	51	69	535	99	56	33	3

## Blueprint

