

Wear Protection Extreema® EP-C



Product information

According to EN-1492 regulations for the safe use of round slings, the sling should always be protected at the attachment point (shackle, pin, axle, etc.) as well as at the hoist (crane hook).

The main application for EP series is to protect the hoist and the object to be lifted for a safer lifting operation.

With Extreema® protection, round slings and lifting slings have a much longer service life and make your working conditions much safer.

The EP-C protector is made from 100% Cordura®. It can be supplied with or without velcro and in various dimensions. It is easy to put on and take off and is the perfect solution for protecting your sling.

The EP-C protection is extremely strong and stretchable. It has proven itself in many industries and for many different applications. The protection prevents damage to the payload; it is resistant to chemicals and extremely resistant to cuts, abrasion and punctures. This makes it perfect for repeated loading of payloads with extremely sharp edges.

Features of Extreema® EP-C protection:

- High durability
- Low elongation
- High flexibility
- High protection against abrasion, tears and heat
- Easy to put on and take off with Velcro fastener

Material: Cordura

Marking: Dyneema

Part Code	Length m	Width mm	Delivery time
8005EPC050	0.5	100	15
8005EPC150	0.5	120	15
8005EPC250	0.5	150	15

8005EPC350	0.5	150	15
8005EPC550	0.5	250	15
8005EPC950	0.5	450	15
8005EPC450	0.5	200	15
8005EPC650	0.5	300	15
8005EPC750	0.5	350	15
8005EPC850	0.5	400	15
8005EPC10050	0.5	500	15
8005EPC1150	0.5	550	15
8005EPC1250	0.5	600	15
8005EPC1350	0.5	700	15
8005EPC1450	0.5	800	15
8005EPC1550	0.5	900	15
8005EPC1650	0.5	1,000	15
8005EPC1100	1	120	15
8005EPC2100	1	150	15
8005EPC0100	1	100	15
8005EPC3100	1	150	15
8005EPC4100	1	200	15
8005EPC5100	1	250	15
8005EPC6100	1	300	15
8005EPC7100	1	350	15
8005EPC8100	1	400	15

8005EPC9100	1	450	15
8005EPC10100	1	500	15
8005EPC11100	1	550	15
8005EPC12100	1	600	15
8005EPC13100	1	700	15
8005EPC14100	1	800	15
8005EPC15100	1	900	15
8005EPC16100	1	1,000	15