



## Stainless Steel Hand Winch MR500-5000

### Product information



This stainless steel hand winch is corrosion resistant and is made of stainless steel 316. The worm gear winch is IP54 classified which means that it is resistant to splashing water and dust on the inside. This makes the winch resistant to the toughest conditions and has a very high corrosion resistance rating.

- winch suitable for lifting and pulling in compliance with EN13157
- static safety factor 4
- load pressure brake with double ratchet system for safe stable hold of the load
- closed gearbox to protect against environmental influence – protection classification IP54
- cable outlet upwards, downwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- stainless steel 316 body, drum, crank and all outgoing parts
- corrosion resistant

#### Options:

- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- ATEX certified zone 2 and 22 (EX)  
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C

**Material:** Stainless steel AISI 316

**Marking:** According to standard

**Standard:** EN 13157

**Note:** Steel, stainless steel or fiber ropes must be ordered separately

**Safety factor:** 4:1

Part Code	WLL ton	Model	Rope Ø mm	Rope capacity m	Capacity top layer kg	Weight kg	Delivery time
5013000500000610	0.5	MR500 SST	6	78.2	224	16	10
5013001500000610	1.5	MR1500 SST	10	41.3	846	30	10
5013003000000610	3	MR3000 SST	14	68.7	1,667	104	10
5013005000000610	5	MR5000 SST	18	42.9	3,276	135	10

## Blueprint

