

Spur Gear Hand Winch TL300-600

Product information

This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semiclosed housing. In short, a fine, easy winch!

- · robust and safe lifting and pulling winch
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards
- adjustable crank
- · suitable for wall mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
 CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
 CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

Material: Steel

Marking: According to standard, CE-marked Temperature range: -20°C up to +70°C

Finish: Painted, grey Standard: EN 13157

Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

Part Code	Code	WLL ton	For rope Ø mm	Rope capacity m	Capacity top layer kg	Weight kg	Delivery time
501300030000560	TL300	0.3	4	35,4	172	10	10
501300060000560	TL600	0.6	6	12,3	336	11	10

Blueprint

