

## Thimble G-414, Crosby - Extra heavy

### Product information

**General:**

The use of the G-414 extra heavy thimbles for your wire rope slings ensures a greater protection against wear of the wire rope and deformation of the wire rope eye.

**Features:**

- Longer service life.

**Material:** Steel

**Marking:** According to standard

**Finish:** Hot-dip galvanised

**Standard:** EN 13411-1



| Part Code    | Rope Ø range mm | Finish     | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg/100pc | Delivery time |
|--------------|-----------------|------------|------|------|------|------|------|------|------|------|-----------------|---------------|
| 123100700230 | 6-7             | Galvanized | 55.5 | 41.4 | 38.1 | 22.4 | 11,2 | 7.1  | 1.5  | 5.85 | 3               | 30            |
| 123100800230 | 8               | Galvanized | 63.5 | 47.8 | 46   | 26.9 | 14,0 | 8.65 | 2.05 | 7.1  | 5.35            | 30            |
| 123101000230 | 9-10            | Galvanized | 73,0 | 54,0 | 54   | 28.7 | 16,8 | 10.4 | 2.8  | 8.65 | 9.8             | 30            |
| 123101200230 | 11-12           | Galvanized | 82.5 | 60.5 | 60.5 | 31.8 | 18.8 | 11.9 | 3.3  | 9.65 | 15.7            | 3             |
| 123101500230 | 13-15           | Galvanized | 92,0 | 70,0 | 70,0 | 38.1 | 23.4 | 13,5 | 3.55 | 10.4 | 23.1            | 30            |
| 123101600230 | 16              | Galvanized | 108  | 82.5 | 79.5 | 44.5 | 26,2 | 16.8 | 4.05 | 12.7 | 34.3            | 30            |
| 123102000230 | 18-20           | Galvanized | 127  | 95.5 | 96,5 | 51   | 33,0 | 19.8 | 5.6  | 16.8 | 72              | 3             |
| 123102200230 | 22              | Galvanized | 140  | 108  | 108  | 57   | 37,3 | 23.9 | 5.6  | 19.1 | 81              | 30            |
| 123102600230 | 24-26           | Galvanized | 156  | 114  | 125  | 63.5 | 44,5 | 26.9 | 6.35 | 22.4 | 142             | 30            |
| 123103200230 | 28-32           | Galvanized | 178  | 130  | 149  | 73   | 47,8 | 33.3 | 6.35 | 28.7 | 181             | 30            |
| 123103500230 | 32-35           | Galvanized | 230  | 165  | 173  | 89   | 57,2 | 36.6 | 9.65 | 28.7 | 402             | 30            |
| 123103800230 | 35-38           | Galvanized | 229  | 159  | 181  | 89   | 66,5 | 39.6 | 12.7 | 28.7 | 587             | 30            |
| 123104000230 | 40              | Galvanized | 286  | 203  | 207  | 102  | 76,2 | 43.7 | 12.7 | 35.1 | 771             | 30            |
| 123104400230 | 44              | Galvanized | 310  | 229  | 216  | 114  | 77,7 | 46.7 | 12.7 | 33.3 | 805             | 30            |
| 123105200230 | 48-52           | Galvanized | 384  | 305  | 264  | 152  | 85,9 | 53,0 | 12.7 | 38.1 | 1,259           | 30            |
| 123105600230 | 56              | Galvanized | 435  | 356  | 302  | 178  | 98,6 | 60.5 | 16,0 | 41.4 | 1,792           | 30            |

# Blueprint

