


Elevator



Certlift 8WF - Elevator

Product information



Typical applications: For elevators.

Features: Fibre core as lubrication reservoir, durable, smooth running, robust design and high flexibility.

Rope construction: 8x19 Warrington + FC.

Marking: According to standard

Finish: Ungalvanized.

Standard: EN 12385-5

Fill factor: 0.44

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm ²	Lubrication	Weight kg/100m	Delivery time
106100804130139	8	1,370/1,770	Bright	sZ	29.9	23.1	SupplierStandard	22.1	30
106100804020139	8	1,570	Bright	sZ	30.5	23.1	SupplierStandard	22.1	30
106100904130139	9	1,370/1,770	Bright	sZ	37.8	29.2	SupplierStandard	28	30
106100904020139	9	1,570	Bright	sZ	38.6	29.2	SupplierStandard	28	30
106101004130139	10	1,370/1,770	Bright	sZ	46.7	36.1	SupplierStandard	34.5	30
106101004020139	10	1,570	Bright	sZ	47.6	36.1	SupplierStandard	34.5	30
106101104130139	11	1,370/1,770	Bright	sZ	56.5	43.7	SupplierStandard	41.8	30
106101104020139	11	1,570	Bright	sZ	57.6	43.7	SupplierStandard	41.8	30
106101204130139	12	1,370/1,770	Bright	sZ	67.2	52	SupplierStandard	49.7	30
106101204020139	12	1,570	Bright	sZ	68.6	52	SupplierStandard	49.7	30
106101304130139	13	1,370/1,770	Bright	sZ	78.9	61	SupplierStandard	58.4	30
106101304020139	13	1,570	Bright	sZ	80.5	61	SupplierStandard	58.4	30
106101404130139	14	1,370/1,770	Bright	sZ	91.5	70.8	SupplierStandard	67.7	30
106101404020139	14	1,570	Bright	sZ	93.3	70.8	SupplierStandard	67.7	30
106101504130139	15	1,370/1,770	Bright	sZ	105	81.2	SupplierStandard	77.7	30
106101504020139	15	1,570	Bright	sZ	107.1	81.2	SupplierStandard	77.7	30
106101604130139	16	1,370/1,770	Bright	sZ	119.5	92.4	SupplierStandard	88.4	30
106101604020139	16	1,570	Bright	sZ	121.9	92.4	SupplierStandard	88.4	30