

Alloy Screw Pin Shackles, Crosby, Wide Body G-2169

Product information

- Capacities of 7, 12.5 and 18 metric tons.
- Proof Load is 2 times the Working Load Limit.
- Individually proof tested and magnetic particle inspected.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductilit design factor, proof load and temperature requirements. Importantly, these shackles meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

Material: Quenched and Tempered for maximum strength. Forged Alloy Steel.

Marking: CE-marked Finish: Galvanized

Safety factor: 5:1

Part Code	WLL ton	B +/25 mm	C mm	D +/02 mm	E mm	G mm	H mm	J mm	K mm	L mm	M mm	P mm	R mm	Weight kg	Delivery time
420100700730	7	31.8	17.5	22.4	46.2	31.8	90.4	40.6	31.8	12.7	101	104	149	1.6	30
420101250730	12.5	42.9	23.4	28.7	60.5	34.8	118	54.1	41.4	14.2	130	140	194	4	30
420101800730	18	51.6	29.5	35.1	68.3	38.1	148	63.5	50.8	17.5	159	172	238	5.9	30

Blueprint

