

Button Spelter Sockets, Crosby, SB-427

Product information



- Available in six sizes from 13 mm - 38 mm.
- Button Spelter terminations have a 100% efficiency rating, based on the catalog strength of the wire rope.
- Designed for use with mobile cranes. Can be used to terminate high performance, rotation resistant ropes, and standard 6 strand ropes.
- Easy to install assembly utilizes Crosby WIRELOCK® socketing compound.
- Sockets and buttons are re-usable.
- Replacement buttons and sockets are available.
- Locking feature available to prevent rotation of rope.
- Button contains cap with eye that can be attached to, and used to pull, rope during reeving process.
- Manufactured to the requirements of API-2C.

Part code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	D mm	E mm	F mm	J mm	K mm	L mm	M mm	Tolerance +/- C mm	Weight kg	Delivery time
122101600265	13-16	27	Painted	202	82	33	30	31	14	38	89	6	74	1.52	1.52	30
122101900265	16-19	45	Painted	240	99	39	35	37	17	44	109	10	87	1.52	1.52	30
122102200265	19-22	57	Painted	275	112	45	41	43	19	52	121	10	101	1.52	1.52	30
122102600265	22-26	82	Painted	327	139	52	51	51	23	62	143	16	115	2.29	2.29	30
122103200265	28-32	136	Painted	378	144	64	57	64	28	75	180	19	145	2.29	2.29	30
122103800265	35-38	161	Painted	459	182	77	70	70	31	92	205	19	172	2.29	2.29	30

Blueprint

