



## Crane End Stop with Padeye ESP

### Product information

End Stops for crane rope applications.

Type ESP has an inspection hole and is prepared for an RFID chip and gives the possibility to check tests and certificates of the product.

**Features:** These end stops are designed for full load applications of rotation resistant and low rotation ropes. The chamfered surface around the cylinder matches different fitting devices. The bore of the end stop is slightly conical to distribute the stress over a larger area.

The exact diameter and length of the end stop assembly should be confirmed when an order is placed to ensure a good match between stop and device.

The end stop is specifically manufactured for rotation resistant and low rotational ropes with a fill factor between 0.61 and 0.76 for other rope types please contact us.

**Material:** Mild carbon steel.

**Marking:** ID code and Manufacturer's symbol.

**Temperature range:** -40°C to 150°C

**Finish:** Ungalvanised.

<b>Part Code</b>	<b>Code</b>	<b>Rope Ø range mm</b>	<b>Finish dia. mm</b>	<b>Finish length mm</b>	<b>Delivery time</b>
1205ESP23D52	ESP23D52	23	52	178	30
1205ESP24D52	ESP24D52	24	52	178	30
1205ESP25D52	ESP25D52	25	52	178	30
1205ESP26D52	ESP26D52	26	52	178	30
1205ESP27D58	ESP27D58	27	58	203	30
1205ESP28D58	ESP28D58	28	58	203	30
1205ESP29D58	ESP29D58	29	58	203	30
1205ESP30D64	ESP30D64	30	64	219	30
1205ESP31D64	ESP31D64	31	64	219	30
1205ESP32D64	ESP32D64	32	64	219	30