

Rope Socket Demag

Product information



- 1) Wire rope Diameter in acc. to DIN EN 12385 (former DIN 3051 – 3071).
- 2) For socketing only use the following materials: DF-VM Art. Nr. 01-7016010, TEGO VG3 Art. Nr. 01-7016028, or Wirelock. Please obtain the socketing guidelines 20612044 (720 IS 817) and DIN EN 13411-4. Socketing Materials´ have the aproval from the Germanischen Lloyd. Weight for socketing material are listed for 1 socket.
- 4) Delivery time on request.

Don't use ropes with bigger diameter as listed in the chart even NOT when the dimension "d" in the chart allows the use of bigger rope diameters.

Material: Permanent rope connectors make it possible to change load handling attachments quickly by simply detaching and connecting the grab ropes to the closing ropes on the hoist unit.

Marking: Producer, Size, Batch No.

Part Code	Rope Ø range mm	Size	G mm	Allowable_dim.	Potting kg ²</SUP>	A mm	e mm	f mm	g mm	r mm	Weight kg	Delivery time
122101800020	18	1.5	5	0.723	560	114	84	21	5	245	1.3	30
122102000020	19-20	2	6	0.78	630	129	84	23	6	310	1.6	30
122102400020	22-24	2	7	1.36	710	140	100	26	7	310	2.4	30
122102600020	26	2	8	1.4	800	158	100	28	8	350	2.6	30
122102800020	28	2	9	2.3	900	171	120	31	9	350	3.6	30
122103200020	32	2	10	2.65	1,000	190	120	32	10	445	4.4	3
122103500020	35	2	11	4.3	1,120	203	142	36	11	445	6	30
122103600020	36	2.5	12	4.1	1,120	225	142	39	12	495	7.5	30
122104000020	40	2.5	13	6.5	1,250	242	166	43	13	555	9	30
122104800020	48	2.5	15	6.7	1,600	286	166	49	15	595	12.5	30
122106400020	64	2.5	17	10	2,100	400	250	75	17	950	30	30