

Lifting Beam Type LO

Product information



This type of lifting beam functions primarily as a spreader beam meaning that a 2-part sling must be used between the crane hook and the lifting beam. The lifting beam is designed with 2x3 attachment points, which makes it possible to have several different types of attachments mounted on the lifting beam at the same time. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.



Part Code	Code	WLL 90° ton	WLL 120° ton	B mm	L mm	L min. mm	L max. mm	Weight kg	Delivery time
6205630051500	LO-0,5/1,5	0.5	0.3	50	1,500	1,300	1,700	12	30
6205630052000	LO-0,5/2	0.5	0.3	50	2,000	1,800	2,200	14	30
6205630052500	LO-0,5/2,5	0.5	0.3	50	2,500	2,300	2,700	16	30
6205630053000	LO-0,5/3	0.5	0.3	50	3,000	2,800	3,200	19	30
6205630101500	LO-1/1,5	1	0.7	70	1,500	1,300	1,700	20	30
6205630053500	LO-0,5/3,5	0.5	0.3	50	3,500	3,300	3,700	21	30
6205630102000	LO-1/2	1	0.7	70	2,000	1,800	2,200	24	30
6205630102500	LO-1/2,5	1	0.7	70	2,500	2,300	2,700	28	30

6205630201500	LO-2/1,5	2	1.2	90	1,500	1,300	1,700	31	30
6205630103000	LO-1/3	1	0.7	70	3,000	2,800	3,200	32	30
6205630103500	LO-1/3,5	1	0.7	70	3,500	3,300	3,700	36	30
6205630202000	LO-2/2	2	1.2	90	2,000	1,800	2,200	37	30
6205630054000	LO-0,5/4	0.5	0.3	70	4,000	3,800	4,200	40	30
6205630202500	LO-2/2,5	2	1.2	90	2,500	2,300	2,700	43	30
6205630055000	LO-0,5/5	0.5	0.3	70	5,000	4,800	5,200	48	30
6205630203000	LO-2/3	2	1.2	90	3,000	2,800	3,200	49	30
6205630302000	LO-3/2	3	2	120	2,000	1,800	2,200	52	30
6205630203500	LO-2/3,5	2	1.2	90	3,500	3,300	3,700	55	30
6205630056000	LO-0,5/6	0.5	0.3	70	6,000	5,800	6,200	56	30
6205630104000	LO-1/4	1	0.7	90	4,000	3,800	4,200	61	30
6205630502000	LO-5/2	5	3	120	2,000	1,800	2,200	68	30
6205630303000	LO-3/3	3	2	120	3,000	2,800	3,200	69	30
6205630105000	LO-1/5	1	0.7	90	5,000	4,800	5,200	73	30
6205630802000	LO-8/2	8	5	140	2,000	1,800	2,200	83	30
6205630106000	LO-1/6	1	0.7	90	6,000	5,800	6,200	85	30
6205630204000	LO-2/4	2	1.2	90	4,000	3,800	4,200	87	30
6205630304000	LO-3/4	3	2	120	4,000	3,800	4,200	87	30
6205630503000	LO-5/3	5	3	120	3,000	2,800	3,200	89	30
6205631002000	LO-10/2	10	6	140	2,000	1,800	2,200	99	30
6205630205000	LO-2/5	2	1.2	100	5,000	4,800	5,200	105	30
6205630803000	LO-8/3	8	5	140	3,000	2,800	3,200	105	30

6205630504000	LO-5/4	5	3	120	4,000	3,800	4,200	110	30
6205630206000	LO-2/6	2	1.2	100	6,000	5,800	6,200	123	30
6205631003000	LO-10/3	10	6	150	3,000	2,800	3,200	123	30
6205630804000	LO-8/4	8	5	140	4,000	3,800	4,200	128	30
6205630305000	LO-3/5	3	2	140	5,000	4,800	5,200	131	30
6205631004000	LO-10/4	10	6	150	4,000	3,800	4,200	147	30
6205630505000	LO-5/5	5	3	120	5,000	4,800	5,200	151	30
6205630306000	LO-3/6	3	2	140	6,000	5,800	6,200	152	30
6205630805000	LO-8/5	8	5	140	5,000	4,800	5,200	171	30
6205630506000	LO-5/6	5	3	120	6,000	5,800	6,200	173	30
6205630806000	LO-8/6	8	5	140	6,000	5,800	6,200	195	30
6205631604000	LO-16/4	16	10	200	4,000	3,800	4,200	205	30
6205631005000	LO-10/5	10	6	150	5,000	4,800	5,200	206	30
6205631605000	LO-16/5	16	10	200	5,000	4,800	5,200	226	30
6205631006000	LO-10/6	10	6	150	6,000	5,800	6,200	233	30
6205631606000	LO-16/6	16	10	200	6,000	5,800	6,200	256	30

Blueprint

