

Lifting Beam Type H

Product information



This type of lifting beam cannot be adjusted and is designed for direct attachment with the crane hook in the central lifting eye. The lifting beam is designed with one attachment point in each corner and is based on lifting assignments in all four points. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Material: Hollow beam and plate manufactured with high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Part Code	Code	WLL	H mm	L1 mm	L2 mm	Weight kg	Delivery time
62056410051500	H-0,5/2-1,5	0.5	255	2,000	1,500	80	30
62056410052000	H-0,5/3-2	0.5	255	3,000	2,000	109	30
62056410052500	H-0,5/4-2,5	0.5	255	4,000	2,500	152	30
62056410151500	H-1,5/2-1,5	1.5	310	2,000	1,500	102	30
62056410152000	H-1,5/3-2	1.5	310	3,000	2,000	139	30
62056410152500	H-1,5/4-2,5	1.5	310	4,000	2,500	216	30
62056410301500	H-3/2-1,5	3	395	2,000	1,500	131	30
62056410302000	H-3/3-2	3	395	3,000	2,000	185	30
62056410302500	H-3/4-2,5	3	395	4,000	2,500	263	30
62056410501500	H-5/2-1,5	5	440	2,000	1,500	193	30
62056410502000	H-5/3-2	5	440	3,000	2,000	275	30
62056410502500	H-5/4-2,5	5	440	4,000	2,500	388	30
62056410801500	H-8/2-1,5	8	555	2,000	1,500	326	30
62056410802000	H-8/3-2	8	555	3,000	2,000	422	30
62056410802500	H-8/4-2,5	8	555	4,000	2,500	565	30
62056411001500	H-10/2-1,5	10	720	2,000	1,500	502	30
62056411002000	H-10/3-2	10	720	3,000	2,000	647	30
62056411002500	H-10/4-2,5	10	720	4,000	2,500	793	30

Blueprint

