



Vertical Lifting Clamp IP10(J)

Product information



The IP10 series vertical lifting clamps are used for the lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed. Usually used as a single point pick or when used with a spreader beam with multiple vertical drop lines. Available in a variety of models:

- IP10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
- IP10J - Larger jaw opening.
- IP10S - For use with Stainless Steel material.
- IP10H - For use with materials with a surface hardness to 472HV10 (450 HB).

Features:

- Available in capacities of .5 thru 30 metric tons
- Higher Working Load Limits are available upon request.
- Wide variety of jaw openings available: 0 to 155 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual and test certificate included with each clamp.
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- For plate surface hardness till 279HV10, only 5% min. WLL is needed.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy Steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Warning: A minimum load of 10% of the WLL is required. Except for WLL 500 kg which requires a minimum load of 5% of WLL.

Safety factor: 4:1

Part code	WLL ton	Jaw width mm	Model	Weight kg	Delivery time
502100050160360	0.5	0-16	0.5-IP10	1.8	30
502100050300360	0.5	15-30	0.5-IP10J	1.8	30
502100100200360	1	0-20	1-IP10	2.2	30
502100200350360	2	0-35	2-IP10	7.6	30
502100300400360	3	0-40	3-IP10	13.8	30
502100450400360	4.5	0-40	4.5-IP10	15	30
502100601000360	6	50-100	6-IP10J	24.5	30
502100900500360	9	0-50	9-IP10	27.5	30
502100901000360	9	50-100	9-IP10J	28.5	30
502101200540360	12	0-54	12-IP10	49	30
502101201080360	12	54-108	12-IP10J	58	3
502101600640360	16	5-64	16-IP10	68	30
502101601280360	16	64-128	16-IP10J	80	30
502102250800360	22.5	5-80	22.5-IP10	124	30
502102251550360	22.5	80-155	22-IP10J	131	30
502103000800360	30	5-80	30-IP10	124	30
502103001550360	30	50-155	30-IP10J	147	30

Blueprint

