



Snatch Block McKissick 419 with Shackle - Light Champion

Product information

The McKissick snatch block 419 Light Champion from Crosby is a snatch block fitted with a shackle. Available from WLL 2 up to 15 T. Can be delivered with bronze bushing (BB) and from WLL 8 T also with roller bearing (RB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Material: Forged steel.

Marking: CE-marked

Safety factor: 4:1

| Part Code | Code | Rope Ø range mm | WLL ton | Sheave dia. mm | Bearing Code | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg | Delivery time |
|--------------|-----------|-----------------|---------|----------------|--------------|------|------|------|------|------|------|------|------|-----------|---------------|
| 424100200200 | 419 w/eye | 8-10 | 2 | 76 | BB | 220 | 76 | 67 | 168 | 14 | 14 | 35 | 35 | 1.8 | 30 |
| 424100200205 | 419 | 8-10 | 2 | 76 | BB | 235 | 76 | 67 | 185 | 13 | 13 | 34 | 40 | 2.3 | 30 |
| 424100400200 | 419 | 10-13 | 4 | 114 | BB | 340 | 108 | 79 | 268 | 16 | 18 | 43 | 51 | 5.4 | 30 |
| 424100800200 | 419 | 16-19 | 8 | 152 | BB | 481 | 152 | 106 | 373 | 32 | 32 | 76 | 88 | 12.7 | 30 |
| 424100800205 | 419 | 16-19 | 8 | 152 | RB | 481 | 152 | 106 | 373 | 32 | 32 | 76 | 88 | 12.7 | 30 |
| 424100800206 | 419 | 16-19 | 8 | 203 | BB | 533 | 206 | 106 | 398 | 32 | 32 | 76 | 88 | 15 | 30 |
| 424100800207 | 419 | 16-19 | 8 | 203 | RB | 533 | 206 | 106 | 398 | 32 | 32 | 76 | 88 | 15 | 30 |
| 424100800208 | 419 | 16-19 | 8 | 254 | BB | 586 | 257 | 106 | 425 | 32 | 32 | 76 | 88 | 19.5 | 30 |
| 424100800209 | 419 | 16-19 | 8 | 254 | RB | 586 | 257 | 106 | 425 | 32 | 32 | 76 | 88 | 19.5 | 30 |
| 424100800201 | 419 | 16-19 | 8 | 305 | BB | 657 | 308 | 106 | 471 | 32 | 32 | 76 | 88 | 24.9 | 30 |
| 424100800203 | 419 | 16-19 | 8 | 356 | BB | 695 | 359 | 106 | 484 | 32 | 32 | 76 | 88 | 30.4 | 30 |
| 424100800204 | 419 | 16-19 | 8 | 356 | RB | 695 | 359 | 106 | 484 | 32 | 32 | 76 | 88 | 30.4 | 30 |
| 424101500200 | 419 | 19-22 | 15 | 406 | BB | 806 | 409 | 129 | 559 | 38 | 44 | 79 | 79 | 59 | 30 |
| 424101500205 | 419 | 19-22 | 15 | 406 | RB | 806 | 409 | 129 | 559 | 38 | 44 | 79 | 79 | 59 | 30 |
| 424101500206 | 419 | 22-26 | 15 | 457 | BB | 842 | 460 | 129 | 559 | 38 | 44 | 79 | 78 | 72.1 | 30 |
| 424101500207 | 419 | 22-26 | 15 | 457 | RB | 841 | 460 | 129 | 565 | 38 | 44 | 79 | 79 | 72.1 | 30 |

Blueprint

