

Swivel Bearing Hoist Hook X-175N



Product information

- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

Material: Alloy steel - quenched and tempered

Marking: CE-marked, Batch number, grade, chain size

Finish: Blue painted.

Safety factor: 4:1

Grade: 10

Part Code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	G mm	H mm	K mm	L mm	P mm	P1 mm	T mm	Weight kg	Delivery time
420500250920	CC	7-8	2.5	36	29	26	13	90	27	145	184	24	20	22	1	3
420500400920	DD	10	4	41	35	29	16	102	29	172	217	28	25	24	1.6	30
420500670920	EE	13	6.7	46	44	38	21	122	38	218	277	35	31	31	3.3	30
420501000920	FF	16	10	61	50	49	23	160	48	261	332	43	39	35	5.6	30
420501600920	GG	18-20	16	74	82	62	25	196	56	327	410	61	57	47	9.5	3
420501900920	HH	22	19	97	96	65	33	221	64	372	471	72	62	56	16	3
420502650920	JJ	26	26.5	123	116	71	51	277	76	469	599	86	81	68	33.5	3
420504000920	KK	32	40	123	116	87	51	353	93	503	651	89	83	76	45	3

Blueprint

