

## Load Hook HS/S Grade 10 - Eye/Latch



### Product information

Eye Load hook - Sling hook with safety latch for general lifting applications.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Standard:** EN 1677-2

(+ 25% WLL)

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	Chain diameter mm	WLL ton	EWL mm	a mm	b mm	d1 mm	d2 mm	e mm	g1 mm	h mm	Weight kg	Delivery time
402300140420	HS/S-6-10	6	1.4	85	17	68	20	10	85	19	21	0.29	3
402300250420	HS/S-7/8-10	7-8	2.5	106	19	88	25	11	106	26	27	0.57	3
402300400420	HS/S-10-10	10	4	131	26	109	34	16	131	31	33	1.19	3
402300670420	HS/S-13-10	13	6.7	164	33	134	43	19	164	39	44	1.96	30
402301000420	HS/S-16-10	16	10	183	40	155	50	25	183	45	50	3.85	3
402301600420	HS/S-19/20-10	19	16	205	48	178	55	27	205	53	55	5.92	3
402301900420	HS/S-22-10	22	19	225	50	196	60	29	225	62	62	7.65	3
402302650420	HS/S-26-10	26	26.5	259	70	235	70	37	259	73	75	12.76	30

# Blueprint

