



# 1 Special Clevis Sub-Assembly GTKR/SUN

## Product information

**General:** For 1-leg slings.

**Temperature range:** -40 °C up to 200 °C

**Safety factor:** 4:1

**Grade:** 12

| Part Code    | Code          | Chain diameter | WLL ton | can be used with single hook acc. DIN15401 up to nr. | d mm | t mm | w mm | e mm | Weight kg | Delivery time |
|--------------|---------------|----------------|---------|--|------|------|------|------|-----------|---------------|
| 403100240070 | GTKR/SUN 1-7  | 7              | 2.36    | 4  | 14   | 120  | 70   | 163  | 0.66      | 30            |
| 403100300070 | GTKR/SUN 1-8  | 8              | 3       | 5  | 17   | 140  | 80   | 183  | 0.92      | 30            |
| 403100500070 | GTKR/SUN 1-10 | 10             | 5       | 6  | 19   | 160  | 95   | 211  | 1.55      | 30            |
| 403100800070 | GTKR/SUN 1-13 | 13             | 8       | 10   | 27   | 190  | 110  | 254  | 3.34      | 30            |
| 403101220070 | GTKR/SUN 1-16 | 16             | 12.2    | 12   | 30   | 190  | 110  | 268  | 4.92      | 30            |

# Blueprint

